

ipcc

INTERGOVERNMENTAL PANEL ON climate change
Working Group III – Mitigation of Climate Change

Annex III:

Technology-specific cost and performance parameters

A report accepted by Working Group III of the IPCC but not approved in detail.

Note:

This document is the copy-edited version of the final draft Report, dated 17 December 2013, of the **Working Group III contribution to the IPCC 5th Assessment Report "Climate Change 2014: Mitigation of Climate Change" that was accepted but not approved in detail by the 12th Session of Working Group III and the 39th Session of the IPCC on 12 April 2014 in Berlin, Germany.** It consists of the full scientific, technical and socio-economic assessment undertaken by Working Group III.

The Report should be read in conjunction with the document entitled "Climate Change 2014: Mitigation of Climate Change. Working Group III Contribution to the IPCC 5th Assessment Report - Changes to the underlying Scientific/Technical Assessment" to ensure consistency with the approved Summary for Policymakers (WGIII: 12th/Doc. 2a, Rev.2) and presented to the Panel at its 39th Session. This document lists the changes necessary to ensure consistency between the full Report and the Summary for Policymakers, which was approved line-by-line by Working Group III and accepted by the Panel at the aforementioned Sessions.

Before publication, the Report (including text, figures and tables) will undergo final quality check as well as any error correction as necessary, consistent with the IPCC Protocol for Addressing Possible Errors. Publication of the Report is foreseen in September/October 2014.

Disclaimer:

The designations employed and the presentation of material on maps do not imply the expression of any opinion whatsoever on the part of the Intergovernmental Panel on Climate Change concerning the legal status of any country, territory, city or area or of its authorities, or concerning the delimitation of its frontiers or boundaries.

Chapter:	A.III	
Title:	Annex III – Technology-specific cost and performance parameters	
Author(s):	Editor:	Steffen Schlömer
	LAs:	Thomas Bruckner, Lew Fulton, Edgar Hertwich, Alan McKinnon, Daniel Perczyk, Joyashree Roy, Roberto Schaeffer, Steffen Schlömer, Ralph Sims, Pete Smith, Ryan Wisser
	CAs:	Gesine Haensel, David de Jager, Maarten Neelis

Annex III: Technology-specific cost and performance parameters

Contents

A.III.1 Introduction.....	3
A.III.2 Energy Supply	4
A.III.2.1 Approach	4
A.III.2.2 Data	6
A.III.3 Transport	11
A.III.3.1 Approach	11
A.III.3.2 Data	13
A.III.4 Industry	24
A.III.4.1 Introduction.....	24
A.III.4.2 Approaches and Data by Industry Sector	25
A.III.4.2.1 Cement	25
A.III.4.2.2 Iron and Steel.....	28
A.III.4.2.3 Chemicals.....	31
A.III.4.2.4 Pulp and Paper.....	34
A.III.4.2.5 Municipal Solid Waste (MSW)	37
A.III.4.2.6 Domestic Wastewater	39
A.III.5 AFOLU.....	40
A.III.5.1 Introduction.....	40
A.III.5.2 Approach	40
A.III.5.2.1 Baseline Emission Intensities.....	40
A.III.5.2.2 Improved emission intensities.....	40
A.III.5.2.3 Levelized Cost of Conserved/Sequestered Carbon	41
References	42

A.III.1 Introduction

Annex III contains data on technologies and practices that have been collected to produce a summary assessment of the potentials and costs of selected mitigation options in various sectors as displayed in Figure 7.7, Table 8.3, Figures 10.7, 10.8, 10.9, 10.10, 10.19, 10.21, Figure 11.16 as well as in corresponding figures in the Technical Summary.

The nature and quantity of mitigation options, as well as data availability and quality of the available data, vary significantly across sectors. Even for largely similar mitigation options, a large variety of context-specific metrics is used to express their cost and potentials that involve conversions of input data into particular output formats. For the purpose of the Fifth Assessment Report (AR5), a limited but still diverse set of sector-specific metrics is used to strike a balance between harmonization of approaches across sectors and adequate consideration of the complexities involved.

Mitigation potentials are approached via product-specific or service-specific emission intensities, i.e., emissions per unit of useful outputs, which are as diverse as electricity, steel, and cattle meat. Mitigation potentials on a product/service level can be understood as the potential reduction in specific emissions that can result from actions such as switching to production processes that cause lower emissions for otherwise comparable products¹ and reducing production/consumption of emission-intensive products.

Mitigation costs are approached via different levelized cost metrics, which share a common methodological basis but need to be interpreted in very different ways. A detailed introduction to the metrics used can be found in the Metrics and Methodology (M&M) Annex (Section A.II.3.1). All of these cost metrics are derived under specific conditions that vary in practice and, hence, need to be set by assumption. These assumptions are not always clear from the literature, where such metrics are presented. Hence, comparison of the same metric taken from different studies is not always possible. For this reasons, in the AR5 these metrics are generally re-calculated under specified conditions, e.g., with respect to weighted average cost of capital, based on underlying input parameters that are less sensitive to assumptions. Sensitivities to assumptions made in the AR5 are made explicit. In several cases, however, the availability of data on the parameters needed to re-calculate the relevant cost metric is very limited. In such cases, expert judgment was used to assess information on costs taken directly from the literature.

More detail on sector-specific metrics, the respective input data and assumptions used as well as the conversions required is presented in the sector-specific sections below.

References for data, justifications for assumptions, and additional context is provided in footnotes to the data tables. Footnotes are inserted at the most general level possible, i.e., footnotes are inserted at table headings where they apply to the majority of data, at column/row headings where they apply to the majority of data in the respective column/row, and at individual cells where they apply only to data points or ranges given in individual cells. Cells of input data are coloured light blue, cells of output data resulting from data conversions shown in figures and tables mentioned above are coloured in green, and cells showing intermediate outputs are coloured light red.

¹ Note that comparability of products is not always given even for seemingly similar ones. For instance, in the case of electricity, the timing of production is crucial for the value of the product and reduces the insights that can be derived from simple comparisons of the metrics used here.

A.III.2 Energy Supply

A.III.2.1 Approach

The emission intensity of electricity production (measured in kg CO₂eq/MWh) can be used as a measure to compare the specific greenhouse gas (GHG) emissions of suggested emission mitigation options and those of conventional power supply technologies. With respect to costs, the levelized cost of energy (LCOE), measured in USD₂₀₁₀/MWh, serves the same purpose.²

The calculation of LCOE of a technology requires data on all cash flows that occur during its lifetime (see formula in M&M Annex) as well as on the amount of energy that is provided by the respective technology. Cash flows are usually reported in some aggregate form based on widely deployed monetary accounting principles combining cash flows into different categories of expenditures and revenues that occur at varying points during the lifetime of the investment.

The applied method presents LCOE that include all relevant costs associated with the construction and operation of the investigated power plant in line with the approach in IEA (2010). Taxes and subsidies are excluded, and it is assumed that grids are available to transport the electricity. Additional costs associated with the integration of variable sources are neglected as well (see Section 7.8.2 for an assessment of these costs).

The input data used to calculate LCOE are summarized in Table 1 below. The conversion of input data into LCOE requires the steps outlined in the following:

Levelized cost (LCOE) in USD₂₀₁₀/MWh_e

$$LCOE = \frac{\alpha \cdot I + OM + F}{E} \quad (\text{Equation A.III.1})$$

$$\alpha = \frac{r}{1 - (1 + r)^{-L_T}} \quad (\text{Equation A.III.2})$$

$$I = \frac{C}{L_B} \cdot \sum_{t=1}^{L_B} (1 + i)^t \cdot \left(1 + \frac{d}{(1 + r)^{L_T}}\right) \quad (\text{Equation A.III.3})$$

$$OM = FOM + (VOM - REV + d_v) \cdot E \quad (\text{Equation A.III.4})$$

$$E = P \cdot FLH \quad (\text{Equation A.III.5})$$

$$F = FC \cdot \frac{E}{\eta} \quad (\text{Equation A.III.6})$$

Where:

- LCOE is the levelized cost of electricity.
- α is the capital recovery Factor (CRF).
- r is the weighted average cost of capital (WACC – taken as either 5% or 10%).
- I is the investment costs, including finance cost for construction at interest i .

² The merits and shortcomings of this method are discussed in detail in the Metrics and Methodology Annex of the AR5 (Annex II).

- C is the capital costs, excluding finance cost for construction ('overnight cost'). In order to calculate the cost for construction, the overnight costs are equally distributed over the construction period.
- d represent the decommissioning cost. Depending on the data in the literature, this is incorporated as an extra capital cost at the end of the project duration which is discounted to $t = 0$ (using a decommissioning factor d , as in (Equation AIII.3)), or as a corresponding variable cost (d_v , in (Equation AIII.4)). $d = 0.15$ for nuclear energy, and zero for all other technologies (given the low impact on LCOE).
- OM are the net annual operation and maintenance costs; summarizing fixed OM (FOM), variable OM (VOM), and variable by-product revenues (REV). As a default and if not stated explicitly otherwise, carbon costs (e.g., due to carbon taxes or emission trading schemes) are not taken into account in calculating the LCOE values.
- E is the energy (electricity) produced annually, which is calculated by multiplying the capacity (P) with the number of (equivalent) full load hours (FLH).
- F are the annual fuel costs,
 - FC are the fuel costs per unit of energy input, and
 - η is the conversion efficiency (in lower heating value – LHV).
- i is the interest rate over the construction loan (taken as 5%).
- L_T is the project duration (in operation), as defined in IEA (2010).
- L_B is the construction period.

Emission Intensities:

For data, see Table AIII.2 below. For methodological issues and literature sources, see Annex II, Section A.II.9.3.

A.III.2.2 Data

Table A.III.1. Cost and performance parameters of selected electricity supply technologies^{i, ii}

Options	C	L_B Construction time (yr)	FOM	VOM	REV	F
	Overnight capital expenditure (excl. construction interest) (USD ₂₀₁₀ /kW)		Fixed annual O&M cost (USD ₂₀₁₀ /kW) ⁱⁱⁱ	Variable O&M cost (USD ₂₀₁₀ /MWh) ⁱⁱⁱ	Variable by-product revenue (USD ₂₀₁₀ /MWh)	Average fuel price of fuel j (USD ₂₀₁₀ /GJ)
	Min / Median / Max	Avg	Min / Median / Max	Min / Median / Max	Min / Median / Max	Min / Max
Currently Commercially Available Technologies						
Coal – PC ^{iv}	380 / 2200 / 3900	5	0 / 23 / 75	0 / 3.4 / 9.0		2.9 / 5.3
Gas – Combined Cycle ^v	550 / 1100 / 2100	4	0 / 7 / 39	0 / 3.2 / 4.9		3.8 / 14
Biomass – CHP ^{vi}	2000 / 5600 / 11000	4.5	0 / 101 / 400	0 / 0 / 56	4 / 26 / 93 ^{vii}	3.3 / 9.3
Biomass – cofiring ^{vi, viii}	350 / 900 / 1800	1	13 / 20 / 20	0 / 0 / 2		3.3 / 9.3
Biomass – dedicated ^{vi}	1900 / 3600 / 6500	4.5	42 / 99 / 500	0 / 3.8 / 34		3.3 / 9.3
Geothermal ^{ix, x}	1000 / 5000 / 10000	3	0 / 0 / 150	0 / 11 / 31		
Hydropower ^{xi, xii}	500 / 1900 / 8500	5	5 / 35 / 250	0 / 0 / 15		
Nuclear ^{xiii, xiv}	1600 / 4300 / 6400	9	0 / 0 / 110	1.7 / 13 / 30		0.74 / 0.87
Concentrated Solar Power ^{xv, xvi}	3700 / 5100 / 11000	2	0 / 50 / 66	0 / 0 / 35		
Solar PV – rooftop ^{xvii, xviii}	2200 / 4400 / 5300	0	17 / 37 / 44	0 / 0 / 0		
Solar PV – utility ^{xvii, xviii}	1700 / 3200 / 4300	0	12 / 20 / 30	0 / 0 / 0		
Wind onshore ^{xix, xx}	1200 / 2100 / 3700	1.5	0 / 0 / 60	0 / 14 / 26		
Wind offshore ^{xix, xxi}	2900 / 4400 / 6500	3.5	0 / 40 / 130	0 / 16 / 63		
Pre-commercial Technologies						
CCS – Coal – Oxyfuel ^{xxii}	2800 / 4000 / 5600	5	0 / 58 / 140	9.1 / 10 / 12 ^{xxiii}		2.9 / 5.3
CCS – Coal – PC ^{xxii}	1700 / 3300 / 6600	5	0 / 45 / 290	11 / 15 / 28 ^{xxiii}		2.9 / 5.3
CCS – Coal – IGCC ^{xxii}	1700 / 3700 / 6600	5	0 / 23 / 110	12 / 13 / 23 ^{xxiii}		2.9 / 5.3
CCS – Gas – Combined Cycle ^{xxii}	1100 / 2000 / 3800	4	5 / 13 / 73	4.8 / 8.3 / 15 ^{xxiii}		3.8 / 14
Ocean ^{xxiv, xxv}	2900 / 5400 / 12000	2	0 / 78 / 360	0 / 0.16 / 20		

Table A.III.1 (continued). Cost and performance parameters of selected electricity supply technologies^{i, ii}

Options	η	FLH	LT	Decommissioning cost ^{xxvi}	LCOE			
	Plant efficiency for fuel j (%)	Capacity utilization /FLH (hr)	Plant lifetime (yr)		Levelized cost of electricity ⁱ (USD ₂₀₁₀ /MWh)			
					10% WACC, high FLH, 0 USD ₂₀₁₀ /tCO _{2, direct}	5% WACC, high FLH, 0 USD ₂₀₁₀ /tCO _{2, direct}	10% WACC, low FLH, 0 USD ₂₀₁₀ /tCO _{2, direct}	10% WACC, high FLH, 100 USD ₂₀₁₀ /tCO _{2, direct}
	Min / Median / Max	Min / Max	Avg		Min / Median / Max	Min / Median / Max	Min / Median / Max	Min / Median / Max
Currently Commercially Available Technologies								
Coal – PC ^{iv}	33 / 39 / 48	3700 / 7400	40	See endnote xxvi	30 / 78 / 120	27 / 61 / 95	36 / 120 / 190	97 / 150 / 210
Gas – Combined Cycle ^v	41 / 55 / 60	3700 / 7400	30		34 / 79 / 150	31 / 71 / 140	43 / 100 / 170	69 / 120 / 200
Biomass – CHP ^{vi}	14 / 29 / 36	3500 / 7000	30		85 / 180 / 400	71 / 150 / 330	130 / 310 / 610	– ^{xxvii}
Biomass – cofiring ^{vi}	38 / 41 / 48	3700 / 7400	40		65 / 89 / 110	49 / 67 / 88	100 / 140 / 170	160 / 200 / 260 ^{xxviii}
Biomass – dedicated ^{vi}	20 / 31 / 48	3500 / 7000	40		77 / 150 / 320	63 / 130 / 270	120 / 230 / 440	– ^{xxvii}
Geothermal ^{ix, x}		5300 / 7900	30		18 / 89 / 190	12 / 60 / 130	25 / 130 / 260	18 / 89 / 190
Hydropower ^{xi, xii}		1800 / 7900	50		9 / 35 / 150	6 / 22 / 95	40 / 160 / 630	9 / 35 / 150
Nuclear ^{xiii, xiv}	33 / 33 / 34	3700 / 7400	60		45 / 99 / 150	32 / 65 / 94	72 / 180 / 260	45 / 99 / 150
Concentrated Solar Power ^{xv, xvi}		2200 / 3500	20		150 / 200 / 310	110 / 150 / 220	220 / 320 / 480	150 / 200 / 310
Solar PV – rooftop ^{xvii, xviii}		1100 / 2400	25		110 / 220 / 270	74 / 150 / 180	250 / 490 / 600	110 / 220 / 270
Solar PV – utility ^{xvii, xviii}		1200 / 2400	25		84 / 160 / 210	56 / 110 / 130	170 / 310 / 400	84 / 160 / 210
Wind onshore ^{xx, xx}		1800 / 3500	25		51 / 84 / 160	35 / 59 / 120	92 / 160 / 300	51 / 84 / 160
Wind offshore ^{xxi, xx}		2600 / 3900	25		110 / 170 / 250	80 / 120 / 180	160 / 240 / 350	110 / 170 / 250
Pre-commercial Technologies								
CCS – Coal – Oxyfuel ^{xxii}	32 / 35 / 41	3700 / 7400	40	See endnote xxvi	90 / 120 / 170	71 / 100 / 130	140 / 180 / 270	92 / 130 / 180
CCS – Coal – PC ^{xxii}	28 / 30 / 43	3700 / 7400	40		69 / 130 / 200	57 / 110 / 150	97 / 210 / 310	78 / 150 / 210
CCS – Coal – IGCC ^{xxii}	30 / 32 / 35	3700 / 7400	40		75 / 120 / 200	63 / 100 / 150	100 / 180 / 310	85 / 140 / 210
CCS – Gas – Combined Cycle ^{xxii}	37 / 47 / 54	3700 / 7400	30		52 / 100 / 210	45 / 86 / 190	70 / 140 / 270	55 / 110 / 220
Ocean ^{xxiv, xxv}		2000 / 5300	20		82 / 150 / 300	60 / 110 / 210	200 / 390 / 780	82 / 150 / 300

- ⁱ **General:** Note that many input parameters (C, FOM, VOM, and η) are not independent from each other; they come in parameter sets. Parameters that are systematically varied to obtain output values include fuel prices, WACC, and full load hours (FLH). Lifetimes and construction times are set to standard values. The range in levelized cost of electricity (LCOE) results from calculating two LCOE values per individual parameter set, one at a low and one at a high fuel price, for the number of individual parameter sets available per technology. Variation with WACC and with FLHs is shown in separate output columns. This approach is different from the SRREN (IPCC, 2011), where input parameters were considered as independent from each other and the lowest (highest) LCOE value resulted from taking all best-case (worst-case) parameter values.
- ⁱⁱ **General:** Comparison of data on capital expenditures with values presented in SRREN (IPCC, 2011) are only possible to limited degrees, since the datasets used in the AR5 reflect a larger sample of projects (including those with more extreme costs) than in the SRREN.
- ⁱⁱⁱ **General:** Some literature references only report on fixed OM costs (FOM), some only on variable OM costs (VOM), some on both, and some none. The data in the FOM and VOM columns show the range found in literature. Hence, note that these FOM and VOM values cannot be combined to derive total OM costs. The range of levelized costs of electricity shown in the table is the result of calculations for the individual combinations of parameters found in the literature.
- ^{iv} **Coal PC (Pulverized Coal):** Black and Veatch (2012), DEA (2012), IEA/NEA (2010), IEA (2013a), IEA-RETD (2013), Schmidt et al. (2012), US EIA (2013).
- ^v **Gas Combined Cycle:** Black and Veatch (2012), DEA (2012), IEA/NEA (2010), IEA (2011), IEA (2013a), IEA-RETD (2013), Schmidt et al. (2012), US EIA (2013).
- ^{vi} **Biomass:** Black and Veatch (2012), DEA (2012), IPCC-SRREN (2011), IRENA (2012), NREL (2012), US EIA (2013).
- ^{vii} **Biomass CHP (Combined Heat and Power):** Revenues from heat from CHP are assumed to be the natural gas price divided by 90% (this is the assumed reference boiler efficiency). It is assumed that one-third of the heat production is marketable, caused by losses and seasonal demand changes. This income is subtracted from the variable O&M costs (proportional to the amount of heat produced per unit of power), where applicable. Only heat production from biomass-CHP is treated in this manner.
- ^{viii} **Biomass Co-firing:** Capital costs for co-firing as reported in literature (and the summary table) represent an investment to upgrade a dedicated coal power plant to a co-firing installation. The LCOEs shown in the summary table are those of the total upgraded plant. For the calculation of the LCOEs, the capital costs of the co-firing upgrade are added to the median coal PC capital costs. Fuel costs are obtained by weighting coal and biomass costs with their share in the fuel mix (with biomass shares ranging between 5% and 20%). To calculate specific emissions, the dedicated biomass emissions and (pulverized) coal emissions were added, taking into account biomass shares ranging between 5% and 20%. In the direct emissions coal-related emissions are shown, while the biomass related emissions are shown in column n (Biogenic, geogenic CO₂ and albedo), indicating indirect emissions. We applied an efficiency of 35% to the coal part of the combustion.
- ^{ix} **Geothermal:** This category includes both flash steam and binary cycle power plants. Data on costs show wide ranges, depending on specific conditions. Geothermal (binary plant) LCOE averages have increased by 39% since the SRREN (BNEF, and Frankfurt and School-UNEP Centre, 2013). Low-end estimate is from NREL (2012) for a flash plant at higher temperatures; the high-end estimate is from Black and Veatch and based on enhanced geothermal systems, which are not fully commercialized. IRENA (2013) reports values down to 1400 USD₂₀₁₁/kW.
- ^x **Geothermal:** Black and Veatch (2012), IEA (2013a), NREL (2012), Schmidt et al. (2012), UK CCC (2011), US EIA (2013).
- ^{xi} **Hydropower:** This includes both run-of-the-river and reservoir hydropower, over a wide range of capacities. Project data from recent IRENA inventories are incorporated, showing a wider range than reported in IPCC SRREN. High-end of capital expenditures refers to Japan, but other sources also report these higher values.
- ^{xii} **Hydropower:** Black and Veatch (2012), IEA (2013a), IEA-RETD (2013), IRENA (2012), Schmidt et al. (2012), UK CCC (2011), US EIA (2013).
- ^{xiii} **Nuclear:** Limited recent data and/or original data are available in the published literature. More recent, (grey literature) sources provide investment cost and LCOE estimates that are considerably higher than the ones shown here (Brandão et al., 2012). Nuclear fuel prices (per GJ input) are based on fuel cycle costs (usually expressed per MWh generated), assuming a conversion efficiency of 33%. They include the front-end (Uranium mining and milling, conversion, enrichment, and fuel fabrication) and back-end (spent fuel transport, storage, reprocessing, and disposal) costs of the nuclear fuel cycle (see IEA and NEA, 2010).
- ^{xiv} **Nuclear:** IAEA (2012), EPRI (2011), IEA/NEA (2010), Rangel and Lévêque (2012), UK CCC (2011), US EIA (2013).
- ^{xv} **Concentrated Solar Power:** This includes both CSP with storage as well as CSP without storage. To prevent an overestimation of the LCOE for CSP with storage, full load hours were used that are directly linked to the design of the system (in- or excluding storage). Project data from recent IRENA inventories are incorporated, showing a wider range than reported in IPCC SRREN. High-end value comes from IRENA (solar tower, 6-15 hours of storage). Low-end comes from IEA and is supported by IRENA data.
- ^{xvi} **Concentrated Solar Power:** Black and Veatch (2012), IEA (2013a), IRENA (2012), US EIA (2013).
- ^{xvii} **Solar Photovoltaic:** IEA (2013a), IRENA (2013), JRC (2012), LBNL (2013), UK CCC (2011), US EIA (2013).
- ^{xviii} **Solar Photovoltaic:** Solar PV module prices have declined substantially since the SRREN (IPCC, 2011), accounting for much of the decline in capital costs shown here relative to those used in SRREN. The LCOE of (crystalline silicon) photovoltaic systems fell by 57% since 2009 (BNEF, and Frankfurt and School-UNEP Centre, 2013).

^{xix} Wind: Black and Veatch (2012), DEA (2012), IEA (2013a), IEA-RETD (2013), IRENA (2012), JRC (2012), UK CCC (2011), US DoE (2013), US EIA (2013).

^{xx} Wind onshore: High-end of capital expenditures is taken from IEA-RETD study (Mostajo Veiga et al., 2013) for Japan. The capital costs presented here show a higher upper end than in the SRREN, and reflect generally smaller wind projects or projects located in remote or otherwise-costly locations. Data from IRENA for Other Asia and Latin America show cost ranges well beyond SRREN. In some regions of the world, wind projects have been increasingly located in lower-quality wind resource sites since the publication of the SRREN (due in part to scarcity of developable higher-quality sites). The FLHs on wind projects, however, have not necessarily decreased -- and in many cases have increased -- due to a simultaneous trend towards longer rotors and higher hub heights. Wind onshore average LCOE have decreased by 15% (BNEF, and Frankfurt and School-UNEP Centre, 2013).

^{xxi} Wind offshore: Offshore wind costs have generally increased since the SRREN, partially explaining the higher upper-end of the cost range shown here. Average LCOE of offshore wind have increased by 44% (BNEF, and Frankfurt and School-UNEP Centre, 2013). Higher capital expenditures reported here are in line with market experiences, i.e., a tendency to more remote areas, deeper seas, higher construction costs and higher steel prices.

^{xxii} Carbon Dioxide Capture and Storage (CCS): Black and Veatch (2012), DEA (2012), Herzog (2011), IPCC-SRCCS (2005), Klara and Plunkett (2010), US EIA (2013), Versteeg and Rubin (2011), IEA (2011).

^{xxiii} Carbon Capture and Storage: Includes transport and storage costs of USD₂₀₁₀10/tCO₂.

^{xxiv} Ocean: Ocean includes both tidal and wave energy conversion technologies. The high-end of capital expenditures is for wave energy DEA (2012). Since the SRREN, marine wave and tidal average LCOE have increased by 36 and 49% respectively (BNEF, and Frankfurt and School-UNEP Centre, 2013).

^{xxv} Ocean: Black and Veatch (2012), DEA (2012), UK CCC (2011).

^{xxvi} General: Some literature references report decommissioning costs under VOM. If decommissioning costs are not given, default assumptions are made (see 'Definition of additional parameters').

^{xxvii} Biomass: Due to the complexities involved in estimating GHG emissions from biomass, no estimates for LCOE at a positive carbon price are given here.

^{xxviii} Biomass co-firing: Only direct emissions of coal share in fuel consumption is considered to calculate LCOE at a carbon price of 100 USD₂₀₁₀/tCO₂.

Table A.III.2. Emissions of selected electricity supply technologies (gCO₂eq/kWh)ⁱ

Options	Direct emissions	Infrastructure & supply chain emissions	Biogenic CO ₂ emissions and albedo effect	Methane emissions	Lifecycle emissions (incl. albedo effect)
	Min / Median / Max	Typical values			Min / Median / Max
Currently Commercially Available Technologies					
Coal – PC	670 / 760 / 870	9.6	0	47	740 / 820 / 910
Gas – Combined Cycle	350 / 370 / 490	1.6	0	91	410 / 490 / 650
Biomass – cofiring	n.a. ⁱⁱ	-	-	-	620 / 740 / 890 ⁱⁱⁱ
Biomass – dedicated	n.a. ⁱⁱ	210	27	0	130 / 230 / 420 ^{iv}
Geothermal	0	45	0	0	6.0 / 38 / 79
Hydropower	0	19	0	88	1.0 / 24 / 2200
Nuclear	0	18	0	0	3.7 / 12 / 110
Concentrated Solar Power	0	29	0	0	8.8 / 27 / 63
Solar PV – rooftop	0	42	0	0	26 / 41 / 60
Solar PV – utility	0	66	0	0	18 / 48 / 180
Wind onshore	0	15	0	0	7.0 / 11 / 56
Wind offshore	0	17	0	0	8.0 / 12 / 35
Pre-commercial Technologies					
CCS – Coal – Oxyfuel	14 / 76 / 110	17	0	67	100 / 160 / 200
CCS – Coal – PC	95 / 120 / 140	28	0	68	190 / 220 / 250
CCS – Coal – IGCC	100 / 120 / 150	9.9	0	62	170 / 200 / 230
CCS – Gas – Combined Cycle	30 / 57 / 98	8.9	0	110	94 / 170 / 340
Ocean	0	17	0	0	5.6 / 17 / 28

ⁱ For a comprehensive discussion of methodological issues and underlying literature sources see Annex II, Section A.II.9.3.

ⁱⁱ Direct emissions from biomass combustion at the power plant are positive and significant, but should be seen in connection with the CO₂ absorbed by growing plants. They can be derived from the chemical carbon content of biomass and the power plant efficiency. For a comprehensive discussion see Chapter 11, Section 11.13. For co-firing, carbon content of coal and relative fuel shares need to be considered.

ⁱⁱⁱ Indirect emissions for co-firing are based on relative fuel shares of biomass from dedicated energy crops and residues (5-20%) and coal (80-95%).

^{iv} Lifecycle emissions from biomass are for dedicated energy crops and crop residues. Lifecycle emissions of electricity based on other types of biomass are given in Chapter 7, Figure 7.6. For a comprehensive discussion see Chapter 11, Section 11.13.4. For a description of methodological issues see Annex II of this report.

A.III.3 Transport

A.III.3.1 Approach

The following tables provide a limited number of examples of transport modes and technologies in terms of their typical potential CO₂ emissions per passenger kilometre (p-km) and freight tonne kilometre (t-km), now and in the 2030 timeframe. Estimates of mitigation cost ranges (USD₂₀₁₀/tCO₂ avoided) are also provided for the limited set of comparisons where data was available. Mitigation cost ranges for HDVs, shipping, and air travel were taken directly from the literature. For sport utility vehicles (SUVs) and light duty vehicles (LDVs), specific mitigation costs were re-calculated for well-defined conditions based on basic input parameter sets (see equations and data provided below). The methodology to calculate specific mitigation costs, also called levelized cost of conserved carbon (LCCC), is discussed in Annex II. Future estimates of both emission intensities and specific mitigation costs are highly uncertain and depend on a range of assumptions.

The variation in emission intensities reflects variation in vehicle efficiencies together with narrow ranges for vehicle occupancy rates, or reflects estimates extracted directly from the literature. No cost uncertainty analysis was conducted. As mentioned above, mitigation cost ranges for HDVs, shipping, and air travel were taken directly from the literature. A standardized uncertainty range of +/- 100 USD₂₀₁₀/tCO₂ was used for SUVs and LDVs. Some parameters such as CO₂ emitted from electricity generation systems and well-to-wheel CO₂ emission levels from advanced biofuels should be considered as specific examples only.

This approach was necessitated due to a lack of comprehensive studies that provide estimates across the full range of vehicle and technology types. Therefore, possible inconsistencies in assumptions and results mean that the output ranges provided here should be treated with caution. The output ranges shown are more indicative than absolute, as suggested by the fairly wide bands for most emission intensity and mitigation cost results.

The meta-analysis of mitigation cost for alternative road transport options was conducted using a 5% discount rate and an approximate vehicle equipment life of 15 years. No fuel or vehicle taxes were included. Assumptions were based on the literature review provided throughout Chapter 8 and the estimates shown in Tables 8.1 and 8.2. Changes in assumptions could result in quite different results.

Some of the key assumptions are included in footnotes below the tables. Further information is available upon request from authors of Chapter 8.

Where emission intensities and LCCC were re-calculated based on specific input data, those inputs are summarized in Table 1 below. The conversion of input data into emission intensities and LCCC requires the steps outlined in the following:

Emission per useful distance travelled (tCO₂/p-km and tCO₂/t-km)

$$EI = \frac{VEff_i \cdot FCI_i}{OC_i} * \beta \quad \text{(Equation A.III.7)}$$

Where:

- *EI* is the emission intensity
- *VEff* is the typical vehicle efficiency
- *FCI* is the fuel carbon intensity
- *OC* is the vehicle occupancy
- *β* is a unit conversion factor

Levelized Cost of Conserved Carbon (USD₂₀₁₀/tCO₂ conserved)

$$LCCC_r = \frac{\Delta E}{\Delta C} \quad (\text{Equation A.III.8})$$

$$\Delta E = \alpha \Delta I + \Delta F \quad (\text{Equation A.III.9})$$

$$\alpha = \frac{r}{1 - (1 + r)^{-L}} \quad (\text{Equation A.III.10})$$

$$\Delta F = (VEff_i \cdot AD_i \cdot FC_i - VEff_j \cdot AD_j \cdot FC_j) \cdot \gamma \quad (\text{Equation A.III.11})$$

$$\Delta C = (VEff_j \cdot FCI_j \cdot AD_j - VEff_i \cdot FCI_i \cdot AD_i) * \eta \quad (\text{Equation A.III.12})$$

Where:

- ΔE is the annualized travel cost increment
- ΔC is the difference in annual CO₂ emissions of alternative i and baseline vehicle j , i.e., the amount of CO₂ saved
- α is the capital recovery Factor (CRF).
- ΔI is the difference in purchase cost of baseline and the alternative vehicle
- ΔF is the difference in annualized fuel expenditures of alternative i and baseline vehicle j
- r is the weighted average cost of capital (WACC)
- L is the vehicle lifetime
- $VEff$ is the typical vehicle efficiency as above, but in calculations for ΔFC and ΔC average typical vehicle efficiency is used.
- AD is the average annual distance travelled
- FC_i is average unit fuel purchase cost (taxes or subsidies excluded) of fuel used in vehicle i
- γ and η are unit conversion factors

Remarks:

Since annual distance travelled is assumed constant for baseline and replacement, it cancels out and does not affect the LCCC.

Variation in output EI derives from variation of vehicle fuel consumption $VEff$ and vehicle occupancy OC .

A.III.3.2 Data

Table A.III.3. Passenger transport – currently commercially available technologies

	VEff	FCI	OC	ΔI	L	AD
Option	Vehicle fuel consumption (l/100km for fossil fuel, kWh/km for electricity) ⁱ	CO ₂ intensity of fuel ⁱⁱ	Vehicle occupancy (capita) ⁱⁱⁱ	Vehicle price markup on baseline car (Incremental capital expenditure) (USD ₂₀₁₀) ^{iv}	Vehicle lifetime (yrs) ^v	Annual distance travelled (km/yr) ^{vi}
Aviation (commercial, medium to long haul)						
2010 Stock Average	-	73 g/MJ	-	-	-	-
Narrow and Wide Body	-	73 g/MJ	-	baseline	-	-
Rail (Light Rail Car)						
Electric, 600 g CO ₂ /kWh _{el}	1.3–2.0	600 g/kWh	60–80	-	-	-
Electric, 200 g CO ₂ /kWh _{el}	1.3–2.0	200 g/kWh	60–80	-	-	-
Road						
<i>New Busses, Large Size</i>						
Diesel	36–42	3.2 kg/litre	40–50	-	-	-
Hybrid Diesel	25–29	3.2 kg/litre	40–50	-	-	-
<i>New Sport Utility Vehicles (SUV), Mid-Size</i>						
2010 Stock average SUV	10–14	2.8 kg/litre	1.5–1.7	-	15	15,000
Gasoline	9.6–12	2.8 kg/litre	1.5–1.7	baseline	15	15,000
Hybrid Gasoline (25% better)	7.2–9	2.8 kg/litre	1.5–1.7	5000	15	15,000
<i>New Light Duty Vehicles (LDV), Mid-Size</i>						
2010 Stock average LDV	8–11	2.8 kg/litre	1.5–1.7	-	15	15,000
Gasoline	7.8–9	2.8 kg/litre	1.5–1.7	baseline	15	15,000
Hybrid Gasoline (28% better)	5.6–6.5	2.8 kg/litre	1.5–1.7	3000	15	15,000
Diesel	5.9–6.7	3.2 kg/litre	1.5–1.7	2500	15	15,000
CNG	7.8–9	2.1 kg/litre	1.5–1.7	2000	15	15,000
Electric, 600 g CO ₂ /kWh _{el}	0.24–0.3	600 g/kWh	1.5–1.7	16000	15	15,000
Electric, 200 g CO ₂ /kWh _{el}	0.24–0.3	200 g/kWh	1.5–1.7	16000	15	15,000
<i>New 2-Wheelers (Scooter up to 200 cm² cylinder capacity)</i>						
2010 Stock Average	1.5–2.5	2.8 kg/litre	1.1–1.3	-	-	-
Gasoline	1.1–1.9	2.8 kg/litre	1.1–1.3	-	-	-

Table A.III.3 (continued). Passenger transport - currently commercially available technologies

Option	FC Average annual fuel purchase cost (USD ₂₀₁₀ /litre for fossil fuel; UScents ₂₀₁₀ /kWh) ^{vii}	EI Emissions per useful distance travelled (gCO ₂ /p-km)	ΔE Annualized travel cost increment (USD ₂₀₁₀ /yr)	ΔC Annual CO ₂ savings from vehicle switch (tCO ₂ /yr)	LCCC _{5%} Levelized cost of conserved carbon at 5% WACC (USD ₂₀₁₀ /tCO ₂)
Aviation (commercial, medium to long haul)					
2010 Stock Average	-	80–218 ^{viii}	-	-	-
Narrow and Wide Body	-	66–95 ^{ix}	-	-	-200 ^x
Rail (Light Rail Car)					
Electric, 600 g CO ₂ /kWh _{el}	-	10–20	-	-	-
Electric, 200 g CO ₂ /kWh _{el}	-	3.3–6.7	-	-	-
Road					
<i>New Busses, Large Size</i>					
Diesel	-	23–34	-	-	-
Hybrid Diesel	-	16–24	-	-	-
<i>New Sport Utility Vehicles (SUV), Mid-Size</i>					
2010 Stock average SUV	0.81	160–260	-	-	-
Gasoline	0.81	160–220	baseline	baseline	baseline
Hybrid Gasoline (25% better)	0.81	120–170	150	1.1	140
<i>New Light Duty Vehicles (LDV), Mid-Size</i>					
2010 Stock average LDV	0.81	130–200	-	-	-
Gasoline	0.81	130–170	baseline	baseline	Baseline
Hybrid Gasoline (28% better)	0.81	92–120	2.5	1.0	2.6
Diesel	0.81	110–150	-15	0.43	-35
CNG	0.35	97–130	-390	0.83	-470
Electric, 600 g CO ₂ /kWh _{el}	0.12	85–120	1000	1.1	950
Electric, 200 g CO ₂ /kWh _{el}	0.12	28–40	1000	2.7	370
<i>New 2-Wheelers (Scooter up to 200 cm² cylinder capacity)</i>					
2010 Stock Average	-	32–63	-	-	-
Gasoline	-	24–47	-	-	-

ⁱ Vehicle fuel economy estimates for road vehicles based on IEA (2012a) and IEA Mobility Model (MoMo) data values, using averages for stock and new vehicles around the world to establish ranges. For rail, water, and air these estimates are based on a range of studies, see Chapter 8 Section 8.3. Rail estimates were based on expert judgment.

ⁱⁱ CO₂ fuel intensities are based on IPCC (2006). CO₂ intensities of electricity based on generic low and high carbon power systems. Well-to-wheel estimates from a range of sources, and specific examples as indicated in tables.

ⁱⁱⁱ Occupancy rates for trains, buses, SUVs, LDVs, and 2-wheelers based on IEA Mobility Model averages from around the world. Bus and rail represent relatively high intensity usage; average loadings in some countries and regions will be lower.

^{iv} Vehicle purchase price increments for LDVs based primarily on NRC (2013) and IEA (2012a).

^v For LDVs, vehicle lifetime-kilometres set to 156,000 kms based on discounting 15 years and 15,000 km per year. Other vehicle type assumptions depend on literature. No normalization was attempted.

^{vi} Annual distance travelled as described above.

^{vii} Fuel prices are point estimates based on current and projected future prices in IEA (2012b). Variation in relative fuel prices can have significant impacts on transport costs and LCCC. Though no cost uncertainty analysis was performed, cost ranges were used where available and a standardized USD₂₀₁₀100/tCO₂ uncertainty range was added around all final point estimates.

^{viii} Current energy consumption per passenger kilometre is 1.1–3 MJ/p-km (IEA, 2009a).

^{ix} Based on TOSCA (2011, Table S-1). Slightly wider range for new/very new to account for range of load factors and distances.

^x Based on IEA and TOSCA analysis. IEA based on 30 years, 10% discount rate.

Table A.III.4. Passenger transport – future (2030) expected technologiesⁱ

Option	VEff (l/100km)	FCI CO ₂ intensity of fuel ⁱⁱ	OC Vehicle occupancy (capita) ⁱⁱⁱ	ΔI Vehicle price mark-up on baseline car (incremental capital expenditure) (USD ₂₀₁₀) ^{iv}	L Vehicle lifetime (yrs) ^v	AD Annual distance travelled (km/yr) ^{vi}
Aviation						
Narrow Body (20% better)	-	-	-	- ^{vii}	15	-
Narrow Body, Open Rotor Engine (33% better)	-	-	-	- ^{vii}	15	-
Road						
<i>Optimized Sport Utility Vehicles (SUV), Mid-Size</i>						
Gasoline (40% better)	5.8–7.2	2.8 kg/litre	1.5–1.7	3500 ^{viii} , future baseline	15	15,000
Hybrid Gasoline (50% better)	4.8–6 ^{ix}	2.8 kg/litre	1.5–1.7	1200	15	15,000
<i>Optimized Light Duty Vehicles (LDV), Mid-Size</i>						
Gasoline (40% better)	4.7–5.4 ^x	2.8 kg/litre	1.5–1.7	2500 ^{viii} , future baseline	15	15,000
Hybrid Gasoline (50% better)	3.9–4.5 ^{xi}	2.8 kg/litre	1.5–1.7	1000	15	15,000
Hybrid Gasoline/Biofuel (50/50 share) (Assuming 70% less CO ₂ /MJ biofuel than /MJ gasoline)	3.9–4.5 ^{xi}	2.8 kg/litre	1.5–1.7	1000	15	15,000
Diesel Hybrid	3.3–3.8 ^{xii}	3.2 kg/litre	1.5–1.7	1700	15	15,000
CNG Hybrid	3.9–4.5 ^{xi}	2.1 kg/litre	1.5–1.7	1200	15	15,000
Electric, 200 g CO ₂ /kWh _{el}	0.19–0.26 ^{xiii}	200 g/kWh	1.5–1.7	3600	15	15,000

Table A.III.4 (continued). Passenger transport – future (2030) expected technologies

Option	FC Average annual fuel purchase cost (USD ₂₀₁₀ /litre for fossil fuel; UScents ₂₀₁₀ /kWh) ^{xiv}	EI Emissions per useful distance travelled (gCO ₂ /p-km)	ΔE Annualized travel cost increment (USD ₂₀₁₀ /yr)	ΔC Annual CO ₂ savings from vehicle switch (tCO ₂ /yr)	LCCC _{5%} Levelized cost of conserved carbon at 5% WACC (USD ₂₀₁₀ /tCO ₂)
Aviation					
Narrow Body (20% better)	-	-	-	-	0–150
Narrow Body, Open Rotor Engine (33% better)	-	44–63 ^{xv}	-	-	0–350
Road					
<i>Optimized Sport Utility Vehicles (SUV), Mid-Size</i>					
Gasoline (40% better)	0.93	94–130	-190 ^{xvi}	1.8 ^{xvi}	-110 ^{xvi}
Hybrid Gasoline (50% better)	0.93	78–110	-440	2.2	-200
<i>Optimized Light Duty Vehicles (LDV), Mid-Size</i>					
Gasoline (40% better)	0.93	76–100	-230 ^{xvii}	1.4 ^{xvii}	-160 ^{xvii}
Hybrid Gasoline (50% better)	0.93	64–83	-21	0.35	-61
Hybrid Gasoline/Biofuel (50/50 share) (Assuming 70% less CO ₂ /MJ biofuel than /MJ gasoline)	0.93	41–54	38	1.0	39
Diesel Hybrid	0.93	63–83	-15	0.36	-43
CNG Hybrid	0.44	48–63	-310	0.77	-410
Electric, 200 g CO ₂ /kWh _{el}	0.13	23–35	86	1.4	61

ⁱ Only those options, where data was available and where significant advances are expected are listed. Other transport options, such as trains, buses and 2-wheelers will remain relevant means of transport in the future but are not covered due to data limitations.

ⁱⁱ CO₂ fuel intensities are based on IPCC (2006). CO₂ intensities of electricity are based on generic low and high carbon power systems. Well-to-wheel estimates from a range of sources, and specific examples as indicated in tables.

ⁱⁱⁱ Occupancy rates for trains, buses, SUVs, LDVs, 2-wheelers based on IEA Mobility Model averages from around the world. Bus and rail represent relatively high intensity usage; average loadings in some countries and regions will be lower.

^{iv} Future vehicle purchase price mark ups based primarily on NRC (2013) and NRC (2010), also IEA (2009a), TIAX (2011), TOSCA (2011), Horton G. (2010) and other sources.

^v For LDVs, vehicle lifetime-kilometres set to 156,000 kms based on discounting 15 years and 15,000 km per year. Other vehicle type assumptions depend on literature. No normalization was attempted.

^{vi} Annual distance travelled as described above.

^{vii} Horton G. (2010) gives ranges from 100 to 150 for Boeing 737-800 and 350 to 500 for Airbus A380.

^{viii} Relative to 2010 baseline.

^{ix} Based on NRC (2013) and other studies, see Section 8.3.

^x Based on NRC (2013) and other studies, see Section 8.3.

^{xi} Fuel consumption of future hybrid gasoline, hybrid gasoline/biofuel, and hybrid CNG based on NRC (2013) and other studies, see Section 8.3.

^{xii} Fuel consumption of future diesel based on NRC (2013) and other studies, see Section 8.3.

^{xiii} Fuel consumption of future electric based on NRC (2013) and other studies, see Section 8.3.

^{xiv} Future fuel prices based on IEA (2012b). These are point estimates - variation in relative fuel prices can have significant impacts on transport costs and LCCC.

^{xv} Value results from assumption of 33% improvement relative to current new narrow and medium body aircrafts based on TOSCA (2011) and Horton G. (2010).

^{xvi} Relative to 2010 gasoline SUV at 2010 fuel price of 0.81 USD₂₀₁₀/litre.

^{xvii} Relative to 2010 gasoline LDV at 2010 fuel price of 0.81 USD₂₀₁₀/litre.

Table A.III.5. Freight transport – currently commercially available technologies

	VEff	FCI	OC	ΔI	L	AD
Option	Vehicle fuel consumption (l/100km)	CO ₂ intensity of fuel (kg/litre for fossil fuel; g CO ₂ /kWh _{el} for electricity)	Vehicle load (t)	Vehicle price markup on baseline car (Incremental capital expenditure) (USD ₂₀₁₀)	Vehicle lifetime	Annual distance travelled (km/yr)
Aviation (commercial, long haul) ⁱ						
2010 Stock Average	-	-	-	-	-	-
Dedicated Aircraft	-	-	-	-	-	-
Belly-hold	-	-	-	-	-	-
Rail (freight train) ⁱⁱ						
Diesel, light goods	-	-	-	-	-	-
Diesel, heavy goods	-	-	-	-	-	-
Electric, 200g CO ₂ /kWh _{el}	-	-	-	-	-	-
Maritime ⁱⁱⁱ						
Current Average International Shipping	-	-	-	-	-	-
New Large International Container Vessel ^{iv}	-	-	-	-	-	-
Large Bulk Carrier/Tanker ^v	-	-	-	-	-	-
LNG Bulk Carrier ^{vi}	-	-	-	-	-	-
Road ^{vii}						
<i>New Medium Duty Trucks</i>						
2010 Stock Average	16–24	3.2 kg/litre	1.6–1.9	-	-	-
Diesel	14–18	3.2 kg/litre	1.6–1.9	-	-	-
Diesel Hybrid	11–14	3.2 kg/litre	1.6–1.9	-	-	-
CNG	18–23	2.1 kg/litre	1.6–1.9	-	-	-
<i>New Heavy Duty, Long-Haul Trucks</i>						
2010 Stock Average	28–44	3.2 kg/litre	8–12	-	-	-
Diesel	25–32	3.2 kg/litre	8–12	-	-	-
CNG	31–40	2.1 kg/litre	8–12	-	-	-

Table A.III.5 (continued). Freight transport – currently commercially available technologies

Option	FC Average annual fuel purchase cost (USD ₂₀₁₀ /litre for fossil fuel; UScents ₂₀₁₀ /kWh)	EI Emissions per useful distance travelled (gCO ₂ /t-km)	ΔE Annualized travel cost increment (USD ₂₀₁₀ /yr)	ΔC Annual CO ₂ savings from vehicle switch (tCO ₂ /yr)	LCCC _{5%} Levelized cost of conserved carbon at 5% WACC (USD ₂₀₁₀ /tCO ₂)
Aviation (commercial, long haul) ⁱ					
2010 Stock Average	-	550–740	-	-	-
Dedicated Aircraft	-	500–820	-	-	-200 ^{viii}
Belly-hold	-	520–700 ^{ix}	-	-	-
Rail (freight train) ⁱⁱ					
Diesel, light goods	-	26–33	-	-	-
Diesel, heavy goods	-	18–25	-	-	-
Electric, 200g CO ₂ /kWh _{el}	-	6–12	-	-	-
Maritime ⁱⁱⁱ					
Current Average International Shipping	-	10–40	-	-	-
New Large International Container Vessel ^{iv}	-	10–20	-	-	-
Large Bulk Carrier/Tanker ^v	-	3–6	-	-	-
LNG Bulk Carrier ^{vi}	-	9–13	-	-	-
Road^{vii}					
<i>New Medium Duty Trucks</i>					
2010 Stock Average	-	270–490	-	-	-
Diesel	-	240–370	-	-	-
Diesel Hybrid	-	180–270	-	-	-
CNG	-	200–300	-	-	-
<i>New Heavy Duty, Long-Haul Trucks</i>					
2010 Stock Average	-	76–180	-	-	-
Diesel	-	70–130	-	-	-
CNG	-	60–110	-	-	-

ⁱ These baseline carbon intensity values for long haul air freight are based on mean estimates from DEFRA (2013). They relate to Boeing 747 and 757 air freight with an average carrying capacity of 84 tonnes and load factor of 69%. High and low estimates set at 15% above and below the means to reflect differences in the energy efficiency of different aircraft types operating with differing load factors.

ⁱⁱ The carbon intensity values for rail freight are based mainly on analyses by DEFRA (2013) and EcoTransit (2011). Expert judgment has been exercised to allow for international differences in the age, capacity, and efficiency of railway rolling stock and railway operating practices.

ⁱⁱⁱ Estimates are derived mainly from DEFRA (2012). This source presents mean carbon intensity values for particular types and size ranges of vessels. The ranges around these means allow for differences in actual vessel size, loading, and energy efficiency on the basis of expert judgment.

^{iv} Carrying more than 8000 twenty-foot equivalent units (TEU).

^v 100-200,000 dead weight tonnes.

^{vi} 100-200,000 cubic metres.

^{vii} Truck CO₂/tonne-km ranges estimated from NRC (2010) and IEA Mobility Model data for averages for truck load factors around the world; vehicle efficiency estimates primarily from NRC (2010), IEA (2009a) and TIAX (2011). Baseline estimates derived from DEFRA (2013), EcoTransit (2011) and IEA (2009a). High and low estimates allow for variations in vehicle size, weight, age, operation and loading in different parts of the world.

^{viii} Aviation freight cost estimates assumptions similar to passenger. Based on IEA and TOSCA analysis, IEA based on 30 years, 10% discount rate.

^{ix} The allocation of emissions between passenger and freight traffic on belly-hold services conforms to a standard 'freight weighting' method.

Table A.III.6. Freight transport – future (2030) expected technologies

Options ⁱ	VEff	FCI	OC	ΔI	L	AD
	Vehicle fuel consumption (l/100km)	CO ₂ intensity of fuel (kg/litre for fossil fuel; g CO ₂ /kWh _{el} for electricity)	Vehicle load (t)	Vehicle price markup on baseline car (incremental capital expenditure) (USD ₂₀₁₀)	Vehicle lifetime	Annual distance travelled (km/yr)
Aviation (commercial, long haul)						
Improved Aircraft (25% better)	-	-	-	-	-	-
Improved, Open Rotor Engine (33% better)	-	-	-	-	-	-
Maritime						
Optimized Container Vessel	-	-	-	-	-	-
Optimized Bulk Carrier	-	-	-	-	-	-
Roadⁱⁱ						
<i>Optimized Medium Duty Trucks</i>						
Diesel	8–13	3.2 kg/litre	1.6–1.9	-	-	-
<i>Optimized Heavy Duty, Long-Haul Trucks</i>						
Diesel	15–22	3.2 kg/litre	8–12	-	-	-
Diesel/Biofuel (50/50 share) (Assuming 70% less CO ₂ /MJ biofuel than /MJ diesel)	15–22	2.1 kg/litre	8–12	-	-	-

Table A.III.6 (continued). Freight transport – future (2030) expected technologies

Option	FC	EI	ΔE	ΔC	LCCC _{5%}
	Average annual fuel purchase cost (USD ₂₀₁₀ /litre for fossil fuel; UScents ₂₀₁₀ /kWh)	Emissions per useful distance travelled (gCO ₂ /t-km)	Annualized travel cost increment (USD ₂₀₁₀ /yr)	Annual CO ₂ savings from vehicle switch (tCO ₂ /yr)	Levelized cost of conserved carbon at 5% WACC (USD ₂₀₁₀ /tCO ₂)
Aviation (commercial, long haul)					
Improved Aircraft (25% better)		300–450 ⁱⁱⁱ	-	-	150 ^{iv}
Improved, Open Rotor Engine (33% better)		270–400 ⁱⁱⁱ	-	-	350 ^{iv}
Maritime					
Optimized Container Vessel		7–13 ^v	-	-	-100 ^{vi}
Optimized Bulk Carrier		2–4 ^v	-	-	-100 ^{vi}
Roadⁱⁱ					
<i>Optimized Medium Duty Trucks</i>					
Diesel		140–260	-	-	-100
<i>Optimized Heavy Duty, Long-Haul Trucks</i>					
Diesel		41–91	-	-	-250
Diesel/Biofuel (50/50 share) (Assuming 70% less CO ₂ /MJ biofuel than /MJ diesel)		26–59	-	-	-

ⁱ No future rail CO₂ or cost estimates were included due to lack of information.

ⁱⁱ Future truck efficiencies and costs primarily from NRC (2010), Zhao et al (2013).

ⁱⁱⁱ These baseline carbon intensity values for long haul airfreight are based on mean estimates from DEFRA (2013). They relate to Boeing 747 and 757 airfreight with an average carrying capacity of 84 tonnes and load factor of 69%. High and low estimates set at 15% above and below the means to reflect differences in the energy efficiency of different aircraft types operating with differing load factors.

^{iv} Projections of the carbon mitigation costs of future aircraft development are based mainly on Tosca. Mitigation costs for future technologies assumed similar to passenger aircraft since the specific large commercial type aircraft are mostly the same configuration.

^v Estimates are derived mainly from DEFRA (2012). This source presents mean carbon intensity values for particular types and size ranges of vessels. The ranges around these means allow for differences in actual vessel size, loading and energy efficiency on the basis of expert judgment.

^{vi} Shipping cost estimates based primarily on Buhaug (2009), Lloyds Register/DNV (2011), and IEA (2009a) (review of literature).

A.III.4 Industry

A.III.4.1 Introduction

The data presented below has been used to assess typical product-specific CO₂eq emissions (i.e., emission per unit of product)³ for different production practices, which are commercially available today or may become so in the future, and for selected industrial sectors. Both direct and indirect specific emissions are assessed. Specific emissions could be reduced by switching to production processes that cause lower emissions for otherwise comparable products⁴ and by reducing production/consumption of emission-intensive products. Some production practices are mutually exclusive; others can be combined to yield deeper reductions in specific emissions. The impact of decarbonizing electricity supplied for industrial processes has been assessed, too, for well-defined exemplary conditions.

For all input parameters and specific CO₂eq emissions global average values are given as a benchmark. Parameters of individual production practices are generally estimates of typical values based on limited studies and expert judgment. Comparisons of input parameters across different individual production practices and with global averages (see Tables A.III.8–A.III.12 below) yields insights into the intermediate effect via which changes in final specific CO₂eq emissions occur for certain production practices.

Estimates of future global averages in specific CO₂eq emissions are derived for long-term scenarios that stabilized GHG concentrations at about 450ppm CO₂eq and provide data at the necessary level of detail. These can be considered as another rough benchmark for emission intensities that can be achieved with currently available and potential future production practices. Generally, scenarios that provide sufficient detail at the level of industrial subsectors/products are very scarce (2–3 models) and are in many cases derived from the same data source as data for individual production practices (mostly International Energy Agency)⁵. Comparisons of emission intensities in future 450ppm stabilization scenarios with available production practices can yield rough insights into future trends for production practices with different specific emissions, but need to be considered with caution.

Specific mitigation costs have been assessed for all production practices except for the decarbonization of electricity supply, the costs of which are dealt with in Chapter 7 (Section 7.8). Specific mitigation costs are expressed in USD₂₀₁₀/tCO₂ or USD₂₀₁₀/tCO₂eq and take into account total incremental operational and capital costs. Generally, costs of the abatement options shown vary widely between individual regions and from plant to plant. Factors influencing the costs include typical capital stock turnover rates (some measures can only be applied when plants are replaced), relative energy costs, etc. No meta-analysis of such individual cost components has been attempted, however, due to limited data availability. Estimates are based on expert judgment of the limited data that is available. Hence, the estimates of specific mitigation costs should be considered with care and as indicative only.

³ Emissions cannot always be expressed in product-specific terms. In the case of chemicals, products are too heterogeneous to express emissions per unit of product. Hence, global emissions of different production practices/technologies have been assessed for total global chemicals production.

⁴ Note that the extent to which certain production processes can be replaced by others is often constrained by various conditions that need to be considered on a case by case basis. The replacement of blast oxygen steel furnaces by electric arc furnaces, for instance, is limited by availability of scrap.

⁵ Further literature sources are assessed in Chapter 10 (Section 10.7). The data sources assessed in 10.7 could, however, often not be used in the summary assessment mainly due to non-comparability of methodological approaches. Chapter 6 presents more comprehensive scenario assessments including all sectors of the economy, which often comes, however, at the expense of sectoral detail. Chapter 10 (Section 10.10) discusses these scenarios from an industry perspective.

Information on specific emissions of different production practices and associated specific mitigation cost is presented in Figures 10.7–10.10 and in Figures 10.19 and 10.20.

A.III.4.2 Approaches and Data by Industry Sector

A.III.4.2.1 Cement

Direct specific emissions of cement (tCO₂/t cement) are derived from technical parameters via the following equation:

$$EI_{direct} = (1 - \lambda) \cdot clc \cdot (e_{n-el} \cdot FCI_{n-el} + CI_{calc}) \quad (\text{Equation A.III.13})$$

Where

- λ is the percentage of emissions captured and stored via CCS
- clc is the clinker to cement ratio
- e_{n-el} is the specific non-electric energy use, i.e., the non-electric energy use per unit of cement
- FCI_{n-el} is the carbon intensity of the non-electric fuel used
- CI_{calc} is the carbon intensity of the calcination process

Indirect specific emissions of cement (tCO₂/t cement) are derived from specific electricity use and the carbon intensity of electricity:

$$EI_{indirect} = e_{el} \cdot FCI_{el} \quad (\text{Equation A.III.14})$$

Where

- e_{el} is the specific electric energy use, i.e., the electricity use per unit of cement
- FCI_{el} is the carbon intensity of the electricity used

Total specific emissions of cement (tCO₂/t cement) are the sum of both direct and indirect specific emissions:

$$EI_{total} = EI_{direct} + EI_{indirect} \quad (\text{Equation A.III.15})$$

Remarks:

Variation in emission intensity derives from variation in selected input parameters. Individual input parameters are varied systematically, i.e., in accordance with the definition of each production practice, while all other input parameters are kept at global average values.

Data on technical input parameters is also very limited. Sources are specified in footnotes to data entries.

Specific mitigation costs (cost of conserved carbon) are estimated based on expert assessment of limited selected studies. See footnote i for details.

Table A.III.7. Technical parameters and estimates for cost of conserved carbon of cement production processes

Options	clc (%) Clinker to cement ratio	e_{n-el} Non-electric fuel intensity (GJ/t clinker)	FCI_{n-el} CO ₂ intensity of non- electric fuel (tCO ₂ /GJ)	CI_{calc} CO ₂ intensity of calcination process (t CO ₂ /t clinker)	e_{el} Electricity intensity (kWh/t cement)	FCI_{el} CO ₂ intensity of electricity (kgCO ₂ /kWh)	λ CO ₂ capture rate (%)	EI_{direct} Direct emission intensity w/ CCS (tCO ₂ /t cement)	$EI_{indirect}$ Indirect emission intensity (tCO ₂ /t cement)	EI_{total} Total emission intensity (tCO ₂ /t cement)	LCCC Levelized cost of conserved carbon (USD ₂₀₁₀ /tCO ₂) ⁱ
Historical Global Average Data and Future Data for 450ppm Scenarios from Integrated Assessment Models											
Global average (2030) ⁱⁱ	-	-	-	-	-	-	-	-	-	0.38–0.59	
Global average (2050) ⁱⁱ	-	-	-	-	-	-	-	-	-	0.24–0.39	
Global average (2010)	0.8	3.9	0.1	0.51	109	0.46 ⁱⁱⁱ	0	0.72	0.05	0.77	
Currently Commercially Available Technologies											
Best practice energy intensity	0.8	2.9–3.1 ^{iv}	0.1	0.51	80–90 ^v	0.46 ⁱⁱⁱ	0	0.64–0.66	0.037–0.041	0.68–0.70	<0–150
Best practice clinker to cement ratio	0.6–0.7 ^{vi}	3.9	0.1	0.51	109	0.46 ⁱⁱⁱ	0	0.54–0.63	0.05	0.59–0.68	<0–50 ^{vii}
Best practice energy intensity and clinker to cement ratio combined	0.6–0.7 ^{vi}	2.9–3.1 ^{iv}	0.1	0.51	80–90 ^v	0.46 ⁱⁱⁱ	0	0.48–0.57	0.037–0.041	0.52–0.62	<0–150 ^{vii}
Improvements in non- electric fuel mix ^{viii}	0.8	3.9	0.056 ^{ix}	0.51	109	0.46 ⁱⁱⁱ	0	0.58	0.05	0.63	<0–150 ^{vii}
Decarbonization of electricity supply	0.8	3.9	0.1	0.51	109	0–0.39 ^x	0	0.72	0–0.043	0.72–0.76	
Pre-commercial Technologies											
CCS ^{xi}	0.8	3.9	0.1	0.51	109	0.46 ⁱⁱⁱ	75–90	0.072–0.18	0.05	0.12–0.23	50–150 ^{xii}
CCS and fully decarbonized electricity ^{xiii}	0.8	3.9	0.1	0.51	109	0	75–90	0.072–0.18	0	0.072–0.18	

ⁱ Expert judgment based on McKinsey (2009), 2012, IEA (2009b, 2012a), BEE (2012), and others. The costs of the abatement options shown vary widely between individual regions and from plant to plant. Factors influencing the costs include typical capital stock turnover rates (some measures can only be applied when plants are replaced), relative energy costs, etc.

ⁱⁱ Data range is taken from the following models: AIM Enduse model (Akashi et al., 2013), IEA 2DS low demand (IEA, 2012a).

ⁱⁱⁱ Based on global industry-wide average CO₂eq intensity of primary energy used in electricity and heat supply in 2010 (see Chapter 10. Table 10.2)

^{iv} This range is based on best practice operation of 4 to 6 stage pre-heater + pre-calciner kiln technology based on IEA (2009b). Actual operation performance does depend on issues such as moisture content and raw material quality and can be above this range.

^v Best practice electricity consumption is based on IEA (2007).

^{vi} Minimum clinker to cement ratio is for Portland cement according to IEA (2007) is a globally achievable value taking availability of substitutes into account IEA (2009b). Further reductions in the clinker to cement ratio are possible for other types of cement (e.g., fly ash or blast furnace slag cement).

^{vii} For clinker substitution and fuel mix changes, costs depend on the regional availability and price of clinker substitutes and alternative fuels.

^{viii} This is assuming that only natural gas is used as non-electric fuel. Further reductions in non-electric fuel emission intensity are technically possible, e.g., by increased use of biomass.

^{ix} Natural gas fuel emission factor (IPCC, 2006).

^x The upper end of the range is based on natural gas combined cycle (IGCC) with an efficiency of 55% and fuel emission factors from IPCC (2006).

^{xi} CCS: Carbon capture and storage. This option assumes no improvements in fuel mix. Feasibility of CCS depends on global CCS developments. CCS is currently not yet applied in the cement sector.

^{xii} IEA GHG (2008) estimates CCS abatement cost at 63 to 170 USD / tCO₂ avoided.

^{xiii} This option assumes no improvements in non-electric fuel mix.

A.III.4.2.2 Iron and Steel

Direct specific CO₂ emissions of crude steel (tCO₂/t steel) are derived from technical parameters via the following equation:

$$EI_{direct} = (1 - \lambda) \cdot EI_{direct,noCCS} \quad (\text{Equation A.III.16})$$

Where

- λ is the percentage of emissions captured and stored via CCS
- $EI_{direct,noCCS}$ is the direct emission intensity without CCS

Indirect specific CO₂ emissions of crude steel (tCO₂/t steel) are derived from specific electricity use and the carbon intensity of electricity:

$$EI_{indirect} = e_{el} \cdot FCI_{el} \quad (\text{Equation A.III.17})$$

Where

- e_{el} is the specific electric energy use, i.e., the electricity use per unit of crude steel
- FCI_{el} is the carbon intensity of the electricity used

Total specific CO₂ emissions of crude steel (tCO₂/t steel) are the sum of both direct and indirect specific emissions:

$$EI_{total} = EI_{direct} + EI_{indirect} \quad (\text{Equation A.III.18})$$

Remarks:

Data on technical input parameters is limited and almost exclusively based on IEA (2007). Emission intensities of the advanced blast furnace route, the natural gas DRI route, and the scrap-based electric arc furnace route are point estimates of global best practice based on IEA (2007). Since no variation in input parameters could be derived from the literature, output ranges have been constructed as an interval around the mean value based on +/-10% of the respective savings. Where input parameters are set by assumption, they are varied within typical ranges and become the sole source of variation in output values, while all other input parameters are kept at global average values.

Specific mitigation costs (cost of conserved carbon) are estimated based on expert assessment of limited selected studies. See footnote i for details.

Table A.III.8. Technical parameters and estimates for cost of conserved carbon of iron and steel production processes

Options ⁱ	$EI_{direct,noCCS}$ Specific direct CO ₂ emissions w/o CCS ⁱⁱ (tCO ₂ /t steel)	e_{el} Specific electricity consumption (kWh/t steel)	FCI_{el} CO ₂ intensity of electricity (kgCO ₂ /kWh)	λ CO ₂ capture rate ⁱⁱⁱ (%)	EI_{direct} Specific direct CO ₂ emissions w/ CCS ^{iv} (tCO ₂ /t steel)	$EI_{indirect}$ Indirect emission intensity (tCO ₂ /t steel)	EI_{total} Total emission intensity (tCO ₂ /t steel)	LCCC Levelized cost of conserved carbon (USD ₂₀₁₀ /tCO ₂) ^v
Historical Global Average Data and Future Data for 450ppm Scenarios from Integrated Assessment Models								
Global average (2030) ^{vi}	-	-	-	-	-	-	0.92–1.36	
Global average (2050) ^{vi}	-	-	-	-	-	-	0.47–0.84	
Global average (2010)	1.8 ^{vii}	820 ^{viii}	0.46 ^{ix}	0	1.8	0.38	2.2	
Currently Commercially Available Technologies								
Advanced blast furnace route ^x	1.3 ^{xi}	350 ^{xii}	0.46 ^{ix}	0	1.3	0.16	1.5	<0–150
Natural gas DRI route ^{xiii, x}	0.7 ^{xi}	590 ^{xii}	0.46 ^{ix}	0	0.7	0.27	0.97	50–150
Scrap based EAF ^{xiv, x}	0.25 ^{xi}	350 ^{xii}	0.46 ^{ix}	0	0.25	0.16	0.41	<0–50 ^{xv}
Decarbonization of electricity supply	1.8 ^{vii}	820 ^{viii}	0–0.39 ^{xvi}	0	1.8	0–0.32	1.8–2.1	
Pre-commercial Technologies								
CCS ^{xvii}	1.8 ^{vii}	820 ^{viii}	0.46 ^{ix}	75–90	0.18–0.45	0.38	0.56–0.82	50–150
CCS and fully decarbonized electricity ^{xviii}	1.8 ^{vii}	-	0	75–90	0.18–0.45	0	0.18–0.45	

ⁱ Non-electric fuel mix improvements are not listed as an abatement option because a large share of the coal use in the iron and steel industry, via the intermediate production of coke, is an inherent feature of the blast furnace technology. The coke is used to reduce iron ore to iron and for structural reasons in the furnace. The limited data availability did not allow assessing the limited potential related to the part of the fuel use that can be substituted.

ⁱⁱ Direct CO₂ emissions contain all emissions from steel production that are unrelated to electricity consumption.

ⁱⁱⁱ As percentage of specific direct CO₂ emissions in steel production.

^{iv} Direct CO₂ emissions contain all emissions from steel production that are unrelated to electricity consumption.

^v Expert judgment based on McKinsey (2009; 2010), IEA (2009b, 2012a), BEE (2012) and others. The costs of the abatement options shown vary widely between individual regions and from plant to plant. Factors influencing the costs include typical capital stock turnover rates (some measures can only be applied when plants are replaced), relative energy costs, etc.

^{vi} Data range is provided by AIM Enduse model (Akashi et al., 2013) DNE21+ (Sano et al., 2013a; b) and IEA 2DS low demand (IEA, 2012a).

^{vii} IEA (2012a).

^{viii} Derived from IEA (2012a, 2013b).

^{ix} Based on global industry-wide average CO₂eq intensity of primary energy used in electricity and heat supply in 2010 (see Chapter 10, Table 10.2). This is a simplified calculation in line with the method used for other sectors ignoring the practice in many iron and steel plants to use process derived gases (blast furnace gas and basic oxygen furnace gas) for electricity production. The emissions from these derived gases are already included in the direct emissions.

^x Excluding rolling and finishing.

^{xi} Value equals lower bound of total emission intensity in IEA (2007, p. 108, table 5.4) as that is for zero-carbon electricity.

^{xii} Derived from spread in total emission intensity in IEA (2007, p. 108, table 5.4) and using a typical coal emission factor of 0.85.

^{xiii} DRI: direct reduced iron.

^{xiv} EAF: Electric arc furnace.

^{xv} Costs depend heavily on the regional availability and price of scrap.

^{xvi} The upper end of the range is based on natural gas combined cycle (IGCC) with an efficiency of 55% and fuel emission factors from IPCC (2006). The approach taken here is a simplified calculation, consistent with the approach for other sectors and does not explicitly take into account the share of the electricity consumed that is produced with process derived gases (see also footnote ix).

^{xvii} CCS: Carbon capture and storage. This option assumes no improvements in fuel mix.

^{xviii} This option assumes no improvements in non-electric fuel mix

A.III.4.2.3 Chemicals

Global direct CO₂ emissions (GtCO₂) of global chemicals production in 2010 are derived from technical parameters via the following equation:

$$CO2_{direct} = (1 - \lambda) \cdot CO2_{direct,noCCS} \quad (\text{Equation A.III.19})$$

Where

- λ is the percentage of emissions captured and stored via CCS
- $CO2_{direct,noCCS}$ are global direct CO₂ emissions in chemicals production in 2010 without CCS

Global indirect CO₂ emissions (GtCO₂) of global chemicals production in 2010 are derived from global electricity use in chemicals production and the carbon intensity of electricity:

$$CO2_{indirect} = Elec \cdot FCI_{el} \cdot \gamma \quad (\text{Equation A.III.20})$$

Where

- $Elec$ is the global electric energy use in the chemicals sector in 2010
- FCI_{el} is the carbon intensity of the electricity used
- γ is a unit conversion factor of 1/1000

Total global CO₂eq emissions (GtCO₂eq) of chemicals production in 2010 are the sum of direct and indirect CO₂ emissions and CO₂-equivalents of non-CO₂ emissions:

$$CO2e_{total} = CO2_{direct} + CO2_{indirect} + CO2e_{acid} + CO2e_{HFC-22} \quad (\text{Equation A.III.21})$$

Where

- $CO2e_{acid}$ are global direct N₂O emissions from global nitric and adipic acid production expressed in CO₂ equivalents
- $CO2e_{HFC-22}$ are global direct HFC-23 emissions from HFC-22 production expressed in CO₂ equivalents

Remarks:

For most production practices, only central estimates for technical input parameters could be derived from the available literature. Where input parameters are set by assumption, they are varied within typical ranges and become a source of variation in output values. Where no variation in input parameters could be derived from the literature, output ranges have been constructed as an interval around the mean value based on +/-10% of the respective savings.

Specific mitigation costs (cost of conserved carbon) are estimated based on expert assessment of limited selected studies. See footnote iii for details.

Table A.III.9. Technical parameters and estimates for cost of conserved carbon of chemicals production processes

Options	$CO2_{direct,noCCS}$	$CO2e_{acid}$	$CO2e_{HFC-22}$	$Elec$	FCI_{el}	λ	$CO2_{direct}$	$CO2_{indirect}$	$CO2_{total}$	$LCCC$
	Global direct CO_2 emissions w/o CCS (Gt CO_2)	Global non- CO_2 emissions from HFC-22 production (Gt CO_2eq) ⁱ	Global non- CO_2 emissions from adipic and nitric acid production (Gt CO_2eq) ⁱ	Global electricity use (TWh)	CO_2 intensity of electricity (kg CO_2/kWh)	CO_2 capture rate ⁱⁱ (%)	Global direct CO_2 emissions w/ CCS (Gt CO_2)	Global indirect CO_2 emissions (Gt CO_2)	Global total emissions (Gt CO_2eq)	Cost of conserved carbon (USD ₂₀₁₀ /t CO_2) ⁱⁱⁱ
Historical Data and Future Data from IEA ETP 2DS Scenario										
Global total (2030) ^{iv}	-	-	-	1400	-	-	1.5–1.6	-	-	-
Global total (2050) ^{iv}	-	-	-	1400	-	-	1.3	-	-	-
Global total (2010)	1.6 ^v	0.13	0.12	1100 ^{vi}	0.46 ^{vii}	0	1.6	0.51	2.4	-
Currently Commercially Available Technologies										
Best practice energy intensity	1.0 ^{viii}	0.13	0.12	860 ^{ix}	0.46 ^{vii}	0	1.0	0.39	1.7	<0–150
Enhanced recycling, cogeneration and process intensification	1.3 ^x	0.13	0.12	1100 ^{vi}	0.46 ^{vii}	0	1.3	0.51	2.1	20–150
Abatement of N_2O from nitric and adipic acid	1.6 ^v	0.13	0.01 ^{xi}	1100 ^{vi}	0.46 ^{vii}	0	1.6	0.51	2.3	0–50
Abatement of HFC-23 emissions from HFC-22 production	1.6 ^v	0 ^{xii}	0.12	1100 ^{vi}	0.46 ^{vii}	0	1.6	0.51	2.2	0–20
Improvements in non-electric fuel mix ^{xiii}	1.2 ^{xiv}	0.13	0.12	1100 ^{vi}	0.46 ^{vii}	0	1.2	0.51	2.0	<0–150
Decarbonization of electricity supply	1.6 ^v	0.13	0.12	1100 ^{vi}	0–0.39 ^{xv}	0	1.6	0–0.44	1.8–2.3	-
Pre-commercial Technologies										
CCS for ammonia production ^{xvi}	1.6 ^v	0.13	0.12	1100 ^{vi}	0.46 ^{vii}	3.5 ^{xvii}	1.5	0.51	2,3	50–150
CCS ^{xviii}	1.6 ^v	0.13	0.12	1100 ^{vi}	0.46 ^{vii}	75–90	0.16–0.4	0.51	0.92–1.16	50–150
CCS and fully decarbonized electricity ^{xix}	1.6 ^v	0.13	0.12	1100 ^{vi}	0	75–90	0.16–0.4	0	0.41–0.65	-

ⁱ Based on EPA (2013) unless specified otherwise.

ⁱⁱ As percentage of global direct CO₂ emissions in chemicals production.

ⁱⁱⁱ Expert judgment based on McKinsey (2009; 2010), IEA (2009c, 2012a), BEE (2012), and others. The costs of the abatement options shown vary widely between individual regions and from plant to plant. Factors influencing the costs include typical capital stock turnover rates (some measures can only be applied when plants are replaced), relative energy costs, etc.

^{iv} Based on IEA ETP 2DS scenarios with high and low global energy demand (IEA, 2012a).

^v Based on IEA (2012a).

^{vi} Based on IEA (IEA, 2013b). IEA (2012a) provided higher values of 1340 TWh.

^{vii} Based on global industry-wide average CO₂eq intensity of primary energy used in electricity and heat supply in 2010 (see Chapter 10. Table 10.2).

^{viii} Based on global potential for savings of 35% in direct emissions in chemicals production as estimated for 2006 (IEA, 2009c) applied to direct emissions in 2010.

^{ix} Based on potential for electricity savings of 0.91 EJ (IEA, 2012a).

^x Based on global technical potential for saving in primary energy consumption of 4.74 EJ (IEA, 2012a) and assuming that conserved primary energy supply is based on natural gas with an emission factor of 56.2 kg CO₂eq/GJ (2006). This translates into savings in global direct CO₂ emissions of 0.27 GtCO₂eq.

^{xi} Based on a global technical potential to save 85% of non-CO₂ emissions from HFC-22 production (EPA, 2013).

^{xii} Based on a global technical potential to save 100% of non-CO₂ emissions from production of adipic and nitric acid (Miller and Kuijpers, 2011)

^{xiii} This is assuming that only natural gas is used as non-electric fuel. Further reductions in non-electric fuel emission intensity are technically possible, e.g., by increased use of biomass.

^{xiv} Based on the assumption that 23% of direct CO₂ emissions can be saved from a switch to natural gas (IEA, 2009c).

^{xv} The upper end of the range is based on natural gas combined cycle (IGCC) with an efficiency of 55% and fuel emission factors from IPCC (2006).

^{xvi} Ammonia production was 159 Mt in 2010 (IEA, 2012a). According to Neelis et al. (2005), a best practice gas-based ammonia facility produces 1.6 tCO₂/t ammonia, of which 70% are pure CO₂ emissions (1.1 t CO₂/t ammonia). 50% of that pure CO₂ stream is assumed to be used in urea production (0.55 t CO₂/t ammonia). 90% of the remaining 0.55 tCO₂/t ammonia is assumed to be captured. This results in an effective CO₂ capture rate of 3.5% of total emissions in chemicals by application of CCS in ammonia production.

^{xvii} This is the effective rate of CO₂ emissions captured in ammonia production relative to global direct CO₂ emissions in chemicals. See also endnote xvi.

^{xviii} This option assumes no improvements in fuel mix.

^{xix} This option assumes no improvements in non-electric fuel mix.

A.III.4.2.4 Pulp and Paper

Specific direct CO₂ emissions of paper (tCO₂/t paper) are derived from technical parameters via the following equation:

$$EI_{direct} = (1 - \lambda) \cdot EI_{direct,noCCS} \quad (\text{Equation A.III.22})$$

Where

- λ is the percentage of emissions captured and stored via CCS
- $EI_{direct,noCCS}$ is the direct emission intensity without CCS

Indirect specific CO₂ emissions of paper (tCO₂/t paper) are derived from specific electricity use and the carbon intensity of electricity:

$$EI_{indirect} = e_{el} \cdot FCI_{el} \quad (\text{Equation A.III.23})$$

Where

- e_{el} is the specific electric energy use, i.e., the electricity use per tonne of paper
- FCI_{el} is the carbon intensity of the electricity used

Total specific CO₂ emissions of paper (tCO₂/t paper) are the sum of both direct and indirect specific emissions:

$$EI_{total} = EI_{direct} + EI_{indirect} \quad (\text{Equation A.III.24})$$

Remarks:

For most production practices, only central estimates for technical input parameters could be derived from the available literature. Where input parameters are set by assumption, they are varied within typical ranges and become a source of variation in output values. Where no variation in input parameters could be derived from the literature, output ranges have been constructed as an interval around the mean value based on +/-10% of the respective savings.

Specific mitigation costs (cost of conserved carbon) are estimated based on expert assessment of limited selected studies. See footnote iv for details.

Table A.III.10. Technical parameters and estimates for cost of conserved carbon of pulp and paper production processes

Options	$EI_{direct,noCCS}$ Specific direct CO ₂ emissions w/o CCS ⁱ (tCO ₂ /t paper)	e_{el} Specific electricity consumption (kWh/t paper)	FCI_{el} CO ₂ intensity of electricity (kgCO ₂ /kWh)	λ CO ₂ capture rate ⁱⁱ (%)	EI_{direct} Specific direct CO ₂ emissions w/ CCS ⁱⁱⁱ (tCO ₂ /t paper)	$EI_{indirect}$ Indirect emission intensity (tCO ₂ /t paper)	EI_{total} Total emission intensity (tCO ₂ /t paper)	LCCC Cost of conserved carbon (USD ₂₀₁₀ /tCO ₂) ^{iv}
Historical Data and Future Data from IEA ETP 2DS Scenario								
Global average (2030) ^v	-	990–1100 ^{vi}	-	-	0.26–0.30 ^{vi}	-	-	-
Global average (2050) ^v	-	920–950 ^{vi}	-	-	0.16–0.20 ^{vi}	-	-	-
Global average (2010)	0.56 ^{vii}	1,200 ^{viii}	0.46 ^{ix}	0	0.56	0.55	1.1	
Currently Commercially Available Technologies								
Best practice energy intensity	0.48 ^x	1,000 ^{xi}	0.46 ^{ix}	0	0.48	0.46	0.94	<0–150
Co-generation	0.53 ^{xii}	1,200 ^{viii}	0.46 ^{ix}	0	0.53	0.55	1.1	20–50
Decarbonization of electricity supply	0.56 ^{vii}	1,200 ^{viii}	0–0.39 ^{xiii}	0	0.56	0–0.47	0.56–1.0	
Pre-commercial Technologies								
CCS ^{xiv}	0.56 ^{vii}	1,200 ^{viii}	0.46 ^{ix}	75–90	0.056–0.14	0.55	0.61–0.69	50–150
CCS and fully decarbonized electricity ^{xv}	0.56 ^{vii}	1,200 ^{viii}	0–0.39	75–90	0.056–0.14	0–0.47	0.056–0.14	

ⁱ Direct CO₂ emissions w/o CCS contain all emissions from paper production that are unrelated to electricity consumption, including those that could be captured and stored.

ⁱⁱ As percentage of specific direct CO₂ emissions in steel production.

ⁱⁱⁱ Direct CO₂ emissions w/ CCS contain all non-captured emissions from paper production that are unrelated to electricity consumption.

^{iv} Expert judgment based on McKinsey (2009; 2010), IEA (2009b, 2012a), BEE (2012), and others. The costs of the abatement options shown vary widely between individual regions and from plant to plant. Factors influencing the costs include typical capital stock turnover rates (some measures can only be applied when plants are replaced), relative energy costs, etc.

^v Based on IEA ETP 2DS scenarios with high and low global energy demand (IEA, 2012a).

^{vi} Derived from IEA (2012a).

^{vii} Based on global direct emissions of 0.22 GtCO₂ and global paper production of 395 Mt (IEA, 2012a).

^{viii} Based on global electricity consumption in pulp and paper production of 1.7 EJ (IEA, 2013b) and global paper production of 395 Mt (IEA, 2012a).

^{ix} Based on global industry-wide average CO₂eq intensity of primary energy used in electricity and heat supply in 2010 (see Chapter 10. Table 10.2).

^x Based on technical potential for savings in non-electric fuel input of 1.5 GJ/t paper (IEA, 2012a) and assuming no change in the non-electric fuel emission factor of 51 kg CO₂/GJ (derived from IEA, 2012a). This translates into savings in specific direct CO₂ emissions of 77 kg CO₂/t paper.

^{xi} Based on technical potential for saving electricity of 200 kWh/t paper (IEA, 2012a).

^{xii} Based on technical potential for savings in non-electric fuel input of 0.6 GJ/t paper (derived from IEA, 2012a) and assuming that conserved fuel is natural gas with an emission factor of 56.2 kg CO₂eq/GJ (IPCC, 2006). This translates into savings in specific direct CO₂ emissions of 34 kg CO₂/t paper.

^{xiii} The upper end of the range is based on natural gas combined cycle (IGCC) with an efficiency of 55% and fuel emission factors from IPCC (2006).

^{xiv} This option assumes no improvements in fuel mix.

^{xv} This option assumes no improvements in non-electric fuel mix.

A.III.4.2.5 Municipal Solid Waste (MSW)

For waste treatment practices that reduce landfill, specific methane emission (gCH₄/kg MSW) and specific nitrous oxide emissions (gN₂O/ kg MSW) are taken directly from the literature. Methane emission intensities (gCH₄/kg MSW) of conventional and improved landfill options are derived from technical parameters given below. CO₂eq emission intensities (tCO₂eq/t MSW) are calculated using global warming potentials (GWP) of methane and nitrous oxide of 21 and 310, respectively.

$$EI_{CH_4} = MCF \cdot DOC \cdot DOCf \cdot F \cdot (1 - OX) \cdot (1 - R) \cdot \gamma \cdot \eta \quad (\text{Equation A.III.25})$$

Where

- *MCF* is the methane correction factor, $Min(MCF) = 0.6$, $Max(MCF) = 1$
- *DOC* is degradable organic carbon (gC/kg MSW)
- *DOCf* is the fraction of DOC dissimilated, $DOCf = 0.5$
- *F* is the fraction of methane in landfill gas, $F = 0.5$
- *OX* is oxidation factor (fraction)
- *R* is the fraction of recovered methane
- γ is the unit conversion factor of C into CH₄, $\gamma = 16/12$
- η is a unit conversion factor of 1/1000

Values given above are based on Frøiland Jensen and Pipatti (2001) and Pipatti et al (2006), default values.

Variation in specific emissions is from maximum to minimum assuming all input parameters are independently distributed.

Cost are taken from EPA (2013) and based on a 10% WACC.

Table A.III.11. Technical parameters and estimates for cost of conserved carbon of waste treatment practices

Options	DOC	OX	R	EI_{CH_4}	EI_{N_2O}	EI_{CO_2eq}	LCCC
	Degradable organic carbon (g C/kg MSW) ^{i, ii}	Oxidation factor (fraction)	Fraction of recovered CH ₄	CH ₄ emission intensity of MSW (gCH ₄ /kg MSW) ^{i, iii}	N ₂ O emission intensity of MSW (g N ₂ O/kg MSW) ^{i, iii}	CO ₂ eq emission intensity of MSW (tCO ₂ eq/t MSW) ⁱ	Levelized cost of conserved carbon at 10% WACC (USD ₂₀₁₀ /tCO ₂ eq) ^{iv}
	min/max			min/max	min/max	min/max	min/max
Reference: Landfill at MSW disposal site	140 / 210	0	0	42 / 110	~0	0.58 / 1.5	
Reducing MSW landfill							
Composting		-	-	0.0 / 8	0.06 / 0.6	0.019 / 0.35	- 140 / 470
Anaerobic digestion		-	-	0 / 1 / 8	~0	0 / 0.17	150 / 590
Improving MSW landfill practices							
Biocover	140 / 210	0.8 ^v	0	8.5 / 21	~0	0.12 / 0.19	99 / 100
In-situ aeration	140 / 210	0.9	0	4.2 / 11	~0	0.058 / 0.10	99 / 130
Flaring	140 / 210	0	0.6 / 0.85	6.4 / 43	~0	0.087 / 0.35	5.0 / 58
CH ₄ capture for power generation	140 / 210	0	0.6 / 0.9	4.2 / 43	~0	0.058 / 0.35	-37 / 66
CH ₄ capture for heat generation	140 / 210	0	0.6 / 0.9	4.2 / 43	~0	0.058 / 0.35	-70 / 89

ⁱ On wet weight basis.ⁱⁱ Total DOC derived from estimates for regional composition of wastes and fraction of DOC in each type of waste (Pipatti et al., 2006, Tables 2.3 and 2.4)ⁱⁱⁱ Methane emissions intensity of reference and improved landfill practices is based on Frøiland Jensen and Pipatti (2001, Table 3) and approach above, which is based on equation 1 of aforementioned source. Methane emission intensity and nitrous oxide emissions intensity of reduced landfill options is based on IPCC (IPCC, 2006)^{iv} Based on EPA (2013).^v Based on EPA (2006).

A.III.4.2.6 Domestic Wastewater

Specific CO₂eq emissions of wastewater (tCO₂/t BOD₅) are based on IPCC (2006) using the following equation to convert methane emissions.

$$EI_{CO_2e} = MAX_{CH_4} \cdot MCF \cdot GWP_{CH_4} \quad (\text{Equation A.III.26})$$

Where

- MAX_{CH_4} is the maximum CH₄ production
- MCF is the methane correction factor
- GWP_{CH_4} is the global warming potential of methane, $GWP_{CH_4} = 21$

The levelized cost of conserved carbon is taken directly from EPA (2013). The discount rate used by EPA (2013) to derive these values was 10%.

Table A.III.12. Technical parameters and estimates for cost of conserved carbon of wastewater treatment practices.

Options	MAX_{CH_4}	MCF	EI_{CO_2e}	$LCCC$
	Maximum CH ₄ production (kg CH ₄ /kg BOD ₅) ⁱⁱ	Methane Correction Factor (fraction) ⁱⁱ	CO ₂ eq emission intensity (tCO ₂ /t BOD ₅)	Levelized cost of conserved carbon (USD ₂₀₁₀ /tCO ₂ eq) ⁱⁱⁱ
Untreated system: Stagnant sewer (open and warm) ^{iv}	0.6	0.4–0.8	5–10	–
Aerobic wastewater plant (WWTP) ^v	0.6	0.2–0.4	2.5–5	0–530
Centralized wastewater collection and WWTP ^{vi}	0.6	0–0.1	0–1.3	0–530
Aerobic biomass digester with CH ₄ collection ^{vii}	0.6	0–0.1	0–1.3	0–530

ⁱ BOD: Biochemical Oxygen Demand. The amount of dissolved oxygen that biological organisms need in order to break down organic material into CH₄. For domestic wastewater this value is in the range of 110 – 400 mg/ l.

ⁱⁱ Based on IPCC (2006). N₂O emission are neglected, since they do not play a significant role in emissions from domestic wastewater.

ⁱⁱⁱ These values are directly taken from EPA (2013). They are relative to regional baselines.

^{iv} Untreated wastewater that is stored in a stagnant sewer under open and warm conditions.

^v Aerobic wastewater treatment refers to the removal of organic pollutants in wastewater by bacteria that require oxygen to work. Water and carbon dioxide are the end products of the aerobic wastewater treatment process.

^{vi} Centralized wastewater collection improves the reduction efficiency. Processes are the same as for the aerobic treatment plant. Centralized collection of wastewater assumes that in general an infrastructure was established that ensures local wastewater storage in closed tanks and secures (emission impermeable) transport from production site to treatment plant.

^{vii} Anaerobic wastewater treatment is a process whereby bacteria digest bio-solids in the absence of oxygen.

A.III.5 AFOLU

A.III.5.1 Introduction

Figure 11.16 shows ranges for baseline emission intensities of selected agricultural and forestry commodities, emission intensities after application of mitigation options, and specific mitigation costs.

A.III.5.2 Approach

Commodity definitions are taken from the FAOSTAT (2013) database, where ‘cereals’ is the aggregation of 16 cereal crops, ‘rice’ is paddy rice, ‘milk’ is whole, fresh milk from dairy cows, ‘meat’ is meat from cattle only, and wood is ‘roundwood’.

A.III.5.2.1 Baseline Emission Intensities

Baseline emission intensities represent the minimum and maximum of regional averages for five world regions. For agricultural commodities (rice, cereals, milk, and meat), they are calculated based on 11-year averages (2000 – 2010) of total annual CO₂eq emissions and total annual production volumes per region taken from (FAOSTAT, 2013). The following emission categories are considered for the calculation of baseline emission intensities: ‘synthetic fertilizer’ for cereals, ‘rice cultivation’ for paddy rice, and ‘enteric fermentation’ and ‘manure management’ for milk and meat.

For production of roundwood only afforestation and reforestation of idle land is considered. Hence, baseline emission intensities are set to zero.

A.III.5.2.2 Improved emission intensities

Improved emission intensities are derived by deducing product-specific mitigation potentials from baseline emission intensities.

Mitigation options considered in the derivation of product-specific mitigation potentials include ‘improved agronomic practices’, ‘nutrient management’, ‘tillage and residue management’ and ‘agroforestry’ for cereals; ‘rice land management’ for rice; ‘feeding’ and ‘dietary additives’ for milk and meat production; and ‘afforestation and reforestation’ for roundwood production.

For cereals and paddy rice, data on mitigation potentials is provided by Smith et al (2008) as average amount of CO₂eq sequestered per land area for four climate zones. These values are converted into amounts of CO₂eq sequestered per product by multiplication with global average product yields per land area based on FAOSTAT (2013).

For meat and milk, mitigation potentials are provided by Smith et al. (2008) as percentage reductions in emissions per mitigation option (see above) and region for five geographical regions. Minimum, average, and maximum of five regional values per mitigation option are taken and converted into amounts of CO₂eq sequestered per product by multiplication with an unweighted average of regional averages of emissions from enteric fermentation per product derived from FAOSTAT (2013). The derivation of the latter is done by dividing the 11-year (2000–2010) regional averages of emissions from enteric fermentation per commodity by the corresponding 11-year regional averages of the total number of producing animals for five geographical regions and by subsequently taking the unweighted average of those five regional averages. For roundwood, the carbon sequestration potential is calculated for representative tree species (based on FAO (2006) and IPCC (2006)) which match the rotation periods for short-term rotations given by Sathaye et al. (2006) for ten geographical regions. Regional and country averages are calculated based on the highest and lowest values for the ten geographical regions.

A.III.5.2.3 Levelized Cost of Conserved/Sequestered Carbon

Mitigation costs for agricultural mitigation options are taken from Smith et al. (2008) for cereals and paddy rice, and from US-EPA (2013) for milk and meat. For the livestock mitigation options, only the low end of the given cost range is considered. Costs for afforestation and reforestation are based on Sathaye et al., (2006).

References

- Akashi O., T. Hanaoka, T. Masui, and M. Kainuma (2013).** Having global GHG emissions by 2050 without depending on nuclear and CCS, *Climatic Change* (DOI: 10.1007/s10584-013-0942-x), (ISSN: 0165-0009, 1573-1480).
- Augustine C., R. Bain, J. Chapman, P. Denholm, E. Drury, D.G. Hall, E. Lantz, R. Margolis, R. Tresher, D. Sandor, N.A. Bishop, S.R. Brown, G.F. Cada, F. Felker, S.J. Fernandez, A.C. Goodrich, G. Hagerman, G. Heath, S. O’Neil, J. Pauette, S. Tegen, and K. Young (2012).** *Renewable Electricity Futures Study, Vol 2. Renewable Electricity Generation and Storage Technologies*. National Renewable Energy Laboratory (NREL), Golden, CO. 370 pp. Available at: http://www.nrel.gov/analysis/re_futures/.
- BEE (2012).** *Database of Energy Efficiency Measures Adopted by the Winners of the National Awards on Energy Conservations*. Bureau of Energy Efficiency (BEE), Ministry of Power, Government of India.
- Black & Veatch (2012).** *Cost and Performance Data for Power Generation Technologies.: Prepared for the National Renewable Energy Laboratory (NREL)*. Black & Veatch, Golden, CO. 105 pp. Available at: <http://bv.com/docs/reports-studies/nrel-cost-report.pdf%E2%80%8E>.
- BNEF, and Frankfurt, and School-UNEP Centre (2013).** *Global Trends in Renewable Energy Investment 2013, FS UNEP Centre*. Available at: <http://fs-unep-centre.org/publications/global-trends-renewable-energy-investment-2013>.
- Brandão M., G. Heath, and J. Cooper (2012).** What can meta-analyses tell us about the reliability of life cycle assessment for decision support?, *Journal of Industrial Ecology* **16** S3–S7 pp. (DOI: 10.1111/j.1530-9290.2012.00477.x), (ISSN: 10881980).
- Buhaug O., J. Corbett, V. Eyring, O. Endresen, J. Faber, S. Hanayama, and others (2009).** *Second IMO GHG Study 2009*. International Maritime Organization, London, UK. 240 pp. Available at: http://www.imo.org/blast/blastDataHelper.asp?data_id=27795&filename=GHGStudyFINAL.pdf.
- Danish Energy Agency (2012).** *Technology Data for Energy Plants: Generation of Electricity and District Heating, Energy Storage and Energy Carrier Generation and Conversion*. Danish Energy Office; Energinet, Copenhagen. . Available at: http://www.energinet.dk/SiteCollectionDocuments/Danske%20dokumenter/Forskning/Technology_data_for_energy_plants.pdf.
- DEFRA (2012).** *Guidelines to Defra / DECC’s GHG Conversion Factors for Company Reporting*. London. . Available at: <http://www.defra.gov.uk/publications/files/pb13773-ghg-conversion-factors-2012.pdf>.
- Department for Environment, Food and Rural Affairs (2013).** *2013 Government GHG Conversion Factors for Company Reporting: Methodology Paper for Emission Factors*. DEFRA, London, UK. 104 pp. Available at: https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/224437/pb13988-emission-factor-methodology-130719.pdf.
- EPA (2006).** *Global Mitigation of Non-CO₂ Greenhouse Gases*. United States Environmental Protection Agency (EPA), Washington DC. . Available at: <http://www.epa.gov/climatechange/Downloads/EPAactivities/GlobalMitigationFullReport.pdf>.

- EPA (2013).** *Global Mitigation of Non-CO₂ Greenhouse Gases: 2010-2030*. United States Environmental Protection Agency, Washington, D.C. 410 pp. Available at: http://www.epa.gov/climatechange/Downloads/EPAactivities/MAC_Report_2013.pdf.
- EPRI (2011).** *Program on Technology Innovation: Integrated Generation Technology Options: Technical Update, June 2011*. Electric Power Research Institute (EPRI), Palo Alto. . Available at: <http://www.epri.com/abstracts/Pages/ProductAbstract.aspx?ProductId=00000000001022782>.
- FAOSTAT (2013).** FAOSTAT database, *Food and Agriculture Organization of the United Nations* . Available at: <http://faostat.fao.org/>.
- Finkenrath M. (2011).** *Cost and Performance of Carbon Dioxide Capture from Power Generation -- Working Paper*. International Energy Agency, Paris. 47 pp. Available at: http://www.iea.org/publications/freepublications/publication/costperf_ccs_powergen.pdf.
- Frøiland Jensen J.E., and R. Pipatti (2001).** *CH₄ Emissions from Solid Waste Disposal*. Intergovernmental Panel on Climate Change (IPCC), Geneva, Switzerland. 439 pp. Available at: http://www.ipcc-nggip.iges.or.jp/public/gp/bgp/5_1_CH4_Solid_Waste.pdf.
- Herzog H.J. (2011).** Scaling up carbon dioxide capture and storage: From megatons to gigatons, *Energy Economics* **33** 597–604 pp. . Available at: <http://ideas.repec.org/a/eee/eneeco/v33y2011i4p597-604.html>.
- Horton G. (2010).** *Future Aircraft Fuel Efficiencies - Final Report*. UK Department for Transport. 92 pp. Available at: https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/4515/future-aircraft-fuel-efficiency.pdf.
- IAEA (2012).** *Climate Change and Nuclear Power 2012*. International Atomic Energy Agency, Vienna, Austria. 39 pp.
- IEA (2007).** *Tracking Industrial Energy Efficiency and CO₂ Emissions: In Support of the G8 Plan of Action*. International Energy Agency (IEA), Paris. 321 pp. Available at: www.iea.org/publications/freepublications/publication/tracking_emissions.pdf.
- IEA (2009a).** *Transport, Energy and CO₂: Moving toward Sustainability*. International Energy Agency, Paris. 414 pp. Available at: <http://www.iea.org/publications/freepublications/publication/transport2009.pdf>.
- IEA (2009b).** *Energy Technology Transitions for Industry: Strategies for the next Industrial Revolution*. International Energy Agency (IEA), Paris. . Available at: www.iea.org/publications/freepublications/publication/industry2009.pdf.
- IEA (2009c).** *Chemical and Petrochemical Sector - Potential of Best Practice Technology and Other Measures for Improving Energy Efficiency*. International Energy Agency (IEA), Paris. 12 pp.
- IEA (2012a).** *Energy Technology Perspectives 2012: Pathways to a Clean Energy System*. International Energy Agency (IEA), Organisation for Economic Co-Operation and Development (OECD), Paris, 686 pp., (ISBN: 9264174885). .
- IEA (2012b).** *World Energy Outlook 2012*. International Energy Agency (IEA), Paris. 655 pp. Available at: <http://www.worldenergyoutlook.org/publications/weo-2012/>.

IEA (2013a). *Tracking Clean Energy Progress 2013. IEA Input to the Clean Energy Ministerial.* International Energy Agency (IEA), Paris. 149 pp. Available at: http://www.iea.org/publications/TCEP_web.pdf.

IEA (2013b). *Energy Statistics and Energy Balances.* International Energy Agency (IEA), Paris. . Available at: <http://www.iea.org/statistics/>.

IEA GHG (2008). *CO₂ Capture in the Cement Industry.* International Energy Agency (IEA), Paris. 220 pp. Available at: cdn.globalccsinstitute.com/sites/default/files/publications/95751/co2-capture-cement-industry.pdf.

IEA, and NEA (2010). *Projected Costs of Generating Electricity.* International Energy Agency (IEA), OECD Nuclear Energy Agency (NEA), Paris. 215 pp. Available at: <http://www.oecd-nea.org/pub/egc/>.

IFEU Heidelberg, Öko-Institut, and IVE/RMCON (2011). *EcoTransIT World Ecological Transport Information Tool for Worldwide Transports - Methodology and Data.* DB Schenker Germany, International Union of Railways, Berlin, Hannover, Heidelberg. 106 pp. Available at: http://www.ecotransit.org/download/ecotransit_background_report.pdf.

IPCC (2005). *IPCC Special Report on Carbon Dioxide Capture and Storage: Prepared by Working Group III of the Intergovernmental Panel on Climate Change* (B. Metz, O. Davidson, H.C. de Coninck, M. Loos, and L.A. Meyer, Eds.). Cambridge University Press, Cambridge; New York, 431 pp. Available at: http://www.ipcc.ch/pdf/special-reports/srccs/srccs_wholereport.pdf.

IPCC (2006). *2006 IPCC Guidelines for National Greenhouse Gas Inventories Volume 4 Agriculture, Forestry and Other Land Use.* 673 pp. Available at: http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/4_Volume4/V4_00_Cover.pdf.

IPCC (2011). *IPCC Special Report on Renewable Energy Sources and Climate Change Mitigation* (O. Edenhofer, R. Pichs-Madruga, Y. Sokona, K. Seyboth, P. Matschoss, S. Kadner, T. Zwickel, P. Eickemeier, G. Hansen, S. Schlömer, and C. von Stechow, Eds.). Cambridge University Press, Cambridge; New York, 1059 pp.

IRENA (2012). *Renewable Energy Technologies: Cost Analysis Series: Wind Power.* International Renewable Energy Agency (IRENA), Abu Dhabi. 56 pp. Available at: http://www.irena.org/DocumentDownloads/Publications/RE_Technologies_Cost_Analysis-WIND_POWER.pdf.

IRENA (2013). *Renewable Power Generation Cost in 2012: An Overview.* International Renewable Energy Agency (IRENA), Abu Dhabi. 88 pp. Available at: https://www.irena.org/DocumentDownloads/Publications/Overview_Renewable%20Power%20Generation%20Costs%20in%202012.pdf.

JRC, and Institute for Energy and Transport (2012). *PV Status Report 2012.* European Commission Joint Research Centre, Ispra, Italy. 111 pp. Available at: <http://iet.jrc.ec.europa.eu/remea/pv-status-report-2012>.

Klara J.M., and J.E. Plunkett (2010). The potential of advanced technologies to reduce carbon capture costs in future IGCC power plants, *The Ninth International Conference on Greenhouse Gas Control Technologies* 4 112–118 pp. (DOI: 10.1016/j.ijggc.2009.10.006), (ISSN: 1750-5836).

Lacal Arántegui, Roberto, T. Corsatea, and K. Suomalainen (2012). *JRC Wind Status Report. Technology, Market and Economic Aspects of Wind Energy in Europe.* European Commission, Joint Research Centre, Institute for Energy and Transport, Petten, The Netherlands. 66 pp. Available at: http://setis.ec.europa.eu/system/files/LDNA25647ENN_2012_JRC_wind_status_report_FINAL.pdf.

LBNL (2013). *Tracking the Sun VI. An Historical Summary of the Installed Price of Photovoltaics in the United States from 1998 to 2012.* Lawrence Berkeley National Laboratory (LBL), Berkeley, CA. 67 pp. Available at: <http://emp.lbl.gov/sites/all/files/lbnl-6350e.pdf>.

Lloyd's Register and DNV (2011). Air pollution and energy efficiency: estimated CO₂ emissions reductions from introduction of mandatory technical and operational energy efficiency measures for ships. International Maritime Organization.

Del Lungo A., J. Ball, and J. Carle (2006). *Global Planted Forests Thematic Study: Results and Analysis.* Food and Agriculture Organization of the United Nations, Rome, Italy. 168 pp. Available at: <http://www.fao.org/forestry/12139-03441d093f070ea7d7c4e3ec3f306507.pdf>.

McKinsey (2010). *Impact of the Financial Crisis on Carbon Economics: Version 2.1 of the Global Greenhouse Gas Abatement Cost Curve.* McKinsey & Company. . Available at: http://www.mckinsey.com/~media/McKinsey/dotcom/client_service/Sustainability/cost%20curve%20PDFs/ImpactFinancialCrisisCarbonEconomicsGHGcostcurveV21.ashx.

McKinsey & Company (2009). *Pathways to a Low-Carbon Economy: Version 2 of the Global Greenhouse Gas Abatement Cost Curve.* McKinsey & Company. 190 pp. Available at: <https://solutions.mckinsey.com/climatedesk/default.aspx>.

Miller B.R., and L.J.M. Kuijpers (2011). Projecting future HFC-23 emissions, *Atmospheric Chemistry and Physics* **11** 13259–13267 pp. (DOI: 10.5194/acp-11-13259-2011), (ISSN: 1680-7324).

Mostajo Veiga M., P. Farina Alvarez, M. Fernandez- Montes Moraleda, and A. Kleinsorge (2013). *Cost and Business Comparisons of Renewable vs. Non-Renewable Technologies.* International Energy Agency Renewable Energy Technology Deployment (IEA-RETD), Utrecht; Madrid. 212 pp. Available at: <http://iea-retd.org/wp-content/uploads/2013/07/20130710-RE-COST-FINAL-REPORT.pdf>.

Neelis M.L., M. Patel, D.J. Gielen, and K. Blok (2005). Modelling CO₂ emissions from non-energy use with the non-energy use emission accounting tables (NEAT) model, *Resources, Conservation and Recycling* **45** 226–250 pp. (DOI: 10.1016/j.resconrec.2005.05.003), (ISSN: 0921-3449).

NRC (2010). *Technologies and Approaches to Reducing the Fuel Consumption of Medium- and Heavy-Duty Vehicles.* US National Research Council, Washington, D.C. 250 pp.

NRC (2013). *Transitions to Alternative Vehicles and Fuels.* National Academies Press, Washington, D.C., 170 pp., (ISBN: 9780309268523).

Pipatti R., C. Sharma, and M. Yamada (2006). *Chapter 2 Waste Generation, Composition and Management Data.* Intergovernmental Panel on Climate Change (IPCC). . Available at: http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_2_Ch2_Waste_Data.pdf.

Pipatti R., and Svoldal, P. (2006). *Chapter 3 Solid Waste Disposal.* Intergovernmental Panel on Climate Change (IPCC), Geneva. 40 pp. Available at: http://www.ipcc-nggip.iges.or.jp/public/2006gl/pdf/5_Volume5/V5_3_Ch3_SWDS.pdf.

- Rangel L.E., and F. L  v  que (2012).** *Revisiting the Cost Escalation Curse of Nuclear Power: New Lessons from the French Experience*. CERNA, MINES ParisTech, Paris, France. 26 pp. Available at: <http://hal-ensmp.archives-ouvertes.fr/hal-00780566>.
- Sano F., K. Akimoto, and K. Wada (2013a).** Impacts of different diffusion scenarios for mitigation technology options and of model representations regarding renewables intermittency on evaluations of CO₂ emissions reductions, *Climatic Change* 1–12 pp. (DOI: 10.1007/s10584-013-0896-z), (ISSN: 0165-0009, 1573-1480).
- Sano F., K. Wada, K. Akimoto, and J. Oda (2013b).** Assessments of GHG emission reduction scenarios of different levels and different short-term pledges through macro- and sectoral decomposition analyses, *Technological Forecasting and Social Change* (DOI: 10.1016/j.techfore.2013.11.002), (ISSN: 0040-1625).
- Sathaye J., W. Makundi, L. Dale, P. Chan, and K. Andrasko (2006).** GHG mitigation potential, costs and benefits in global forests: a dynamic partial equilibrium approach, *The Energy Journal Special Issue* 127–162 pp. .
- Schmidt T.S., R. Born, and M. Schneider (2012).** Assessing the costs of photovoltaic and wind power in six developing countries, *Nature Climate Change* 2 548–553 pp. (DOI: 10.1038/nclimate1490).
- Smith P., D. Martino, Z. Cai, D. Gwary, H. Janzen, P. Kumar, B. McCarl, S. Ogle, F. O’Mara, C. Rice, B. Scholes, O. Sirotenko, M. Howden, T. McAllister, G. Pan, V. Romanenkov, U. Schneider, S. Towprayoon, M. Wattenbach, and J. Smith (2008).** Greenhouse gas mitigation in agriculture, *Philosophical Transactions of the Royal Society B: Biological Sciences* 363 789–813 pp. (DOI: 10.1098/rstb.2007.2184), (ISSN: 0962-8436).
- TIAX (2011).** *European Union Greenhouse Gas Reduction Potential for Heavy-Duty Vehicles*. National Academy of Sciences, San Francisco, CA. 69 pp.
- TOSCA (2011).** *Techno-Economic Analysis of Aircraft*. Technology Opportunities and Strategies Towards Climate Friendly Transport, Cambridge, UK. 58 pp. Available at: http://www.toscaproject.org/FinalReports/TOSCA_WP2_Aircraft.pdf.
- UK CCC (2011).** *Costs of Low-Carbon Generation Technologies*. Global CCS Institute, London.
- US DoE (2013).** *2012 Wind Technologies Market Report*. Lawrence Berkeley National Laboratory (LBNL), Oakridge, TN. 80 pp. Available at: http://www1.eere.energy.gov/wind/pdfs/2012_wind_technologies_market_report.pdf.
- US EIA (2013).** *Updated Capital Cost Estimates for Utility Scale Electricity Generating Plants*. US Energy Information Administration (EIA), Washington DC. 201 pp. Available at: http://www.eia.gov/forecasts/capitalcost/pdf/updated_capcost.pdf.
- Versteeg P., and E.S. Rubin (2011).** A technical and economic assessment of ammonia-based post-combustion CO₂ capture at coal-fired power plants, *International Journal of Greenhouse Gas Control* 5 1596–1605 pp. (ISSN: 17505836).
- Zhao H., A. Burke, and M. Miller (2013).** Analysis of Class 8 truck technologies for their fuel savings and economics, *Transportation Research Part D: Transport and Environment* 23 55–63 pp. (DOI: 10.1016/j.trd.2013.04.004), (ISSN: 1361-9209).